




MarineTuff™ Offshore and Marine Cable Solutions



Belden offers the industry's largest selection of industrial cables for offshore and marine certified applications

**Be certain.
Belden.**

**Whether you are handling oil,
natural gas or petrochemicals,
working onshore or offshore,
Belden's cable, connectivity and
networking solutions will solve
your toughest problems.**



MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff

About Our MarineTuff Cable Offering



MarineTuff - Safe, Robust Cable for Offshore Applications

Thank you for choosing Belden's MarineTuff cables for your offshore cable needs. Belden is known for providing highly reliable, rugged signal transmission solutions for some of the most demanding applications. With the MarineTuff line of cables, Belden's heritage of rugged signal transmission solutions now extends to offshore applications.

All MarineTuff cables are certified by the American Bureau of Shipping (ABS).

The American Bureau of Shipping (ABS) is one of the governing bodies overseeing the safe construction and operation of ABS-classed vessels, modular offshore drilling units (MODUs) or facilities. Belden MarineTuff cables meet or exceed the requirements set for by ABS for offshore applications.

In addition to ABS certification, our HaloarrestXLink (low smoke zero halogen) cables meet numerous requirements for harsh offshore environments. These include UL 1309 (Marine Shipboard Cable), IEEE 1580 Type P jacketing (IEEE Recommended Practice for Marine Cable for Use on Shipboard and Fixed or Floating Facilities) UL Oil Resistance II, IEEE 1202 & FT4 (Flame Resistance), IEC 60754-1 (Compliant for Halogen Content), and IEC 60754-2 (Compliant for Acid Gas Emissions). In other words, we make the toughest cables around and we've got the certifications to prove it!

For complete details on all of the certifications each product family meets, please see the individual sections contained later in this catalog.

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff

About Belden



Peace of Mind with Zero Downtime

Belden is a long-time leader in offering high-performance data and signal transmission solutions for the industrial environment where reliability is absolutely required to maintain safe operations with zero unplanned downtime.

That's why solutions for the industrial environment – one that imposes harsh or severe working conditions on active devices and media installations – are vital. At one time or another, the signaling components at these facilities will have to withstand the destructive effects of temperature extremes, humidity/moisture, dust, mud, oil and solvents, and the potentially corrosive effects of chemicals. As if those weren't enough, add to the list ultraviolet radiation caused by extensive sunlight, electromagnetic interference and the ever-present danger of fire and explosion.

Whether you are handling oil, natural gas or petrochemicals, working onshore or offshore, Belden's cable, connectivity and networking solutions will solve your toughest problems.

Always the Right Solution

Belden is the world's leading supplier of signal transmission solutions including cable, connectivity and active components for mission-critical applications ranging from industrial automation and alternative power generation through to professional broadcasting. Belden offers an extensive portfolio of highly specialized products for steering, control and field level, which the company produces and markets under its proprietary Belden®, Hirschmann™, and Lumberg Automation™ brands. We would be glad to introduce to you our integrated product palette for industrial applications and the worldwide Belden Service.

You will find further information and technical details online at www.belden.com or contact **Belden Technical Support** directly: **Tel. 1.800.235.3361**

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff

Table of Contents



Table of Contents

About our MarineTuff Cable Offering.....	3
About Belden	4
Table of Contents.....	5
Product Characteristic Symbols.....	6
Fiber Optic Cables	7
Loose Tube Indoor/Outdoor Low Smoke Zero Halogen (LSZH).....	8
Breakout Style Cable Tight Buffer - LSZH Indoor/Outdoor.....	9
Industrial Ethernet Cables	10-12
Category 6 DataTuff Cables Unshielded, 4-Pair, 23 AWG	11-12
UL Control Cables.....	13-34
600 V Type TC Cables, 18 AWG, Shielded, Thermoset Jacket.....	14-17
600 V Type TC Cables, 18 AWG, Shielded, Thermoset Jacket.....	17
600 V Type TC Cables, 16 AWG, Unshielded, Thermoset Jacket.....	18-20
600 V Type TC Cables, 16 AWG, Shielded, Thermoset Jacket.....	20
600 V Type TC Cables, 14 AWG, Unshielded, Thermoset Jacket.....	21-23
600 V Type TC Cables, 14 AWG, Shielded, Thermoset Jacket.....	23
600 V Type TC Cables, 12 AWG, Unshielded, Thermoset Jacket.....	24-26
600 V Type TC Cables, 10 AWG, Unshielded, Thermoset Jacket.....	27-28
600 V Type TC Cables, 8 AWG, Unshielded - 10 AWG Uninsulated Ground Wire, Thermoset Jacket	29
600 V Type TC Cables, 6 AWG, Unshielded - 8 AWG Uninsulated Ground Wire, Thermoset Jacket	30
600 V Type TC Cables, 4 AWG, Unshielded - 8 AWG Uninsulated Ground Wire, Thermoset Jacket	31
600 V Type TC Cables, 2 AWG, Unshielded - 6 AWG Uninsulated Ground Wire, Thermoset Jacket	32
600 V Type TC Cables, 1 AWG to 4/0 AWG, Unshielded, Thermoset Jacket.....	33-34
UL Instrumentation Cables	35-42
600 V Type TC Cables, 18 AWG, Unshielded, Thermoset Jacket.....	36-37
600 V Type TC Cables, 16 AWG, Shielded, Thermoset Jacket.....	38-40
600 V Type TC Cables, 14 AWG, Shielded, Thermoset Jacket.....	41
600 V Type TC Cables, 12 AWG, Shielded, Thermoset Jacket.....	42
Variable Frequency Drive (VFD) Cables.....	43-47
Classic Foil/Braid Design Thermoset Low Smoke Zero Halogen	44-45
Classic Symmetrical Design Thermoset Low Smoke Zero Halogen.....	46-47
Foundation Fieldbus Cables.....	48-52
PROFIBUS DP Cables	53-55
RS-485 Cables	56-58
ControlNet Cables	59-61
Blue Hose Cables.....	62-64
DeviceNet Cables	65-67
A/V and Electronic Cable	68-78
Electronic Audio, Control and Instrumentation Cable	69-70
Audio and Speaker Cable	71-72
Coaxial Broadcast AV Cable	73-74
DataTwist® Nonbonded Pair	75-76
Security Composite Cable.....	77-78
Part Number Index	79-82

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff Product Characteristic Symbols



Type P Jacket



Zero Halogen Jacket



Flame Retardant



Oil Resistant



Low Toxicity



Low Smoke



Low Corrosion

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff™

Industrial Fiber Cables



The demand for enhanced security and high quality data, audio, and video is increasing in the offshore environment. Therefore, the quality and reliability of your fiber optic cables is of increasing importance. MarineTuff fiber products offer quality data, audio, and video functions for offshore structures. For instance, in the event of an electromagnetic surge, fiber guarantees 100% of your communication and the network infrastructure remains available. Furthermore, fiber decreases latency and better supports the high bandwidth demands of your growing auxiliary and surveillance networks. Cost efficiency with bidirectional fiber decreases latency and expenditures of commissioning expansive networks.

In addition to offshore rigs and control room applications, Belden products are widely used in separator stations, metering stations, pumping/compressor stations, LNG processing plants, transportation/storage, refining facilities and shipboards.

The MarineTuff fiber line features all-dielectric cable, but metallic armoring can be added when needed for a specific installation. Cable designs feature flame retardant, thermoplastic buffers/tubes, aramid yarn strength members, optional aluminum armor, overall water-blocking tape and low smoke zero halogen jackets (LSZH).

Key Attributes

- Low smoke zero halogen jacketed
- Aluminum interlock or steel corrugated armoring optional
- Flame retardant
- 10 year warranty

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff Industrial Fiber Cables

Loose Tube Indoor/Outdoor
Low Smoke Zero Halogen (LSZH)



Featured Options:


- Sunlight resistance
- Fully water-blocked
- Singlemode and multimode riser rated LSZH

Certifications/Compliance

- NEC/CEC
- UL Type OFNR/OFRC
- cUL OFNR/OFRC FT-4
- Marine approvals: ABS type approval

Construction:

1. LSZH Outer Jacket
2. Aramid Yarn
3. Central E-Glass Strength Member
4. Water Blocking Tape
5. Blue Buffer Tube



No. of Fibers	Fibers/Bundle	Part No.					OD (Nom)	
		OM1 (62.5/125) Std. 1Gb	OM2 (50/125) Std. 1 Gb	OM3 (50/125) 10 Gb - 300 m	OM4 (50/125) 10 Gb - 550 m	OS2 Single-mode Enhanced	Inch	mm
6	6	B9B830*	B9A830	B9C830*	B9E830	B9W830		
12	12	B9B831*	B9A831	B9C831*	B9E831	B9W831*	.38	9.65
24	12	B9B832	B9A832	B9C832	B9E832	B9W832		
36	12	B9B833	B9A833	B9C833	B9E833	B9W833		
48	12	B9B834	B9A834	B9C834	B9E834	B9W834*	.48	12.18

* Indicates common part numbers.

Standard Jacket Color: Black (non-standard jacket colors are available).

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff Industrial Fiber Cables

Breakout Style Cable

Tight Buffer - LSZH Indoor/Outdoor



Featured Options:


- LSZH
- 900 um tight buffer fibers
- Color coded for easy termination
- Flame retardant
- Direct connectorization
- Also available in a 2.5mm sub-unit

Certifications/Compliance

- NEC/CEC
- UL Type OFNR/OFRC
- cUL OFNR/OFRC FT-4
- Marine approvals: ABS type approval

Construction:

1. LSZH Outer Jacket
2. Central E-Glass Strength Member
3. 2.0mm Subunits with Color Coded Jackets
4. 900 Micron Tight Buffered Fiber
5. Aramid Yarn



No of Fibers	Fibers/ Bundle	Part No.				OD (Nom)	
		OM1 (62.5/125) Std. 1Gb	OM3 (50/125) 10 Gb - 300m	OM4 (50/125) 10 Gb - 550m	"OS2 Single-mode Enhanced"	Inch	mm
2	1	FD1B002HB	FD3B002HB	FD4B002HB	FDSB002HB	.260	6.60
4	1	FD1B004HB	FD3B004HB	FD4B004HB	FDSB004HB	.321	8.15
6	1	FD1B006HB	FD3B006HB	FD4B006HB	FDSB006HB	.358	9.09
10	1	FD1B010HB	FD3B010HB	FD4B010HB	FDSB010HB	.455	11.56
12	1	FD1B012HB	FD3B012HB	FD4B012HB	FDSB012HB	.514	13.06

Standard Jacket Color: for grades 2, 3 and 4 is orange, grades 5 and 6 is aqua and grade SM is yellow (non-standard jacket colors are available).

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff

Industrial Ethernet Cables



Only Belden offers the most comprehensive range of Industrial Ethernet cabling solutions available in the world today – all specifically engineered and ruggedly constructed to ensure optimum network performance and uptime, even in the harshest settings. Belden Industrial Ethernet cables, the DataTuff cable line, are far and away the industry's top choice for signal transmission integrity and consistently reliable electrical performance. Unlike commercial off-the-shelf (COTS) Ethernet cabling, our Category 6 copper-based cables are built Belden-tough to withstand the harsh environmental conditions and mechanical stresses typically present in offshore environments.

Belden Bonded-Pair Cables feature a patented design that bonds individual conductors along their longitudinal axis. This assures an extremely uniform spacing within each twisted pair which is a key factor in maintaining consistent electrical performance and providing optimal RFI immunity. Ideally, this distance should remain fixed and stable along the length of the twisted pair. Installation and termination of cable disturbs this relationship and therefore also affects the cable's electrical performance. Even minor disturbances in the spacing can have a significant impact on the electrical performance, particularly impedance, return loss and crosstalk. Since the two conductors of a Bonded-Pair cable are bonded together, gaps cannot form in between the conductors. The physical integrity of the pair is maintained, resulting in consistent electrical performance.

The normal cable installation stresses routing around and through tight passages typical of offshore facilities can impact cable reliability. In a recent survey, contractors indicated that Bonded-Pair cables maintain their physical integrity (and electrical performance) requiring less troubleshooting and re-work.

The performance of the entire network in a marine vessel or offshore facility depends on the integrity and reliability of the cables connecting network devices. A weak or compromised section of the cabling puts the entire network in jeopardy. The MarineTuff suite of Industrial Ethernet cabling is the best choice to meet these challenges.

Key Attributes

- LSZH jackets on all cables and options
- Bronze braid options on all cables and options
- ABS certified, DNV (pending)
- 10 year warranty
- Consistently reliable electrical performance
- Bonded Pair Technology

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff Industrial Ethernet Cables

Category 6, DataTuff® Cables
Unshielded, 4-Pair, 23 AWG



Features:

- 600V UL AWM
- Sunlight and Oil resistant
- Bonded Pairs
- Oil Res II (Thermoset)


Certifications/Compliance

- ABS certified, DNV (pending)
- NEC: CMG
- CEC: CMG
- EtherNet/IP compliant
- FT4/IEEE 1202
- IEC 60332-3-22
- IEC 60754-1 (Jacket)
- IEC 60754-2 (Jacket)

Construction:

1. LSZH Thermoplastic or Thermoset Jacket
2. Internal Tape Separator
3. Four Bonded Pairs
4. Solid Copper Conductor

NOTE: Also available on all options, bronze braid armor with LSZH second jacket not pictured



MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff Industrial Ethernet Cables

Category 6, DataTuff® Cables

Shielded and Unshielded, 4-Pair, 23 AWG



Part No.	Nominal OD		Additional Features/Ratings	
	Inch	mm		
23 AWG, Shielded				
Solid BC Conductors • Polyolefin Insulation • Flame resistant Polyolefin inner Jacket • Overall Beldfoil Shielding • LSZH Outer Jacket				
Thermoset Jacket				
7953Z		Under development	CMG-LS, Category 6	
Thermoplastic Jacket				
7953T		Under development		
23 AWG, Unshielded				
Solid BC Conductors • Polyolefin Insulation • LSZH Outer Jacket				
Thermoset Jacket				
7940Z	0.295	7.4	CMG-LS, Category 6	
Thermoplastic Jacket				
7940T	0.295	7.4		
23 AWG, Shielded with Bronze Braid Armor				
Solid BC Conductors • Polyolefin Insulation • Flame resistant Polyolefin inner Jacket • Overall Beldfoil Shielding • LSZH Outer Jacket				
Thermoset Jacket				
977953Z		Under development	CMG-LS, Category 6	
Thermoplastic Jacket				
777953T		Under development		
23 AWG, Unshielded with Bronze Braid Armor				
Solid BC Conductors • Polyolefin Insulation • LSZH Outer Jacket				
Thermoset Jacket				
977940Z	0.43	11.1	CMG-LS, Category 6	
Thermoplastic Jacket				
777940T	0.43	11.1		

Conductor Color Codes: Pair 1: White/Blue Stripe & Blue • Pair 2: White/Orange Stripe & Orange • Pair 3: White/Green Stripe & Green • Pair 4: White/Brown Stripe & Brown

All reels of Bonded Pair cable come with bonded pair separator tool (part no. 1797B)
 EtherNet/IP is a trademark of ODVA. To learn more visit <http://www.belden.com/products/industrialcable/ethernet-ip.cfm>
 BC = Bare Copper

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff

UL Control and Instrumentation Cables



MarineTuff certified Belden instrumentation and control cables bring reliable, safety conscious wiring solutions to offshore platforms, equipment suppliers and commercial shipbuilders. These ABS-certified cables offer physical toughness and the safety benefits of low smoke and zero halogen (LSZH) jackets to provide a no-compromise solution that can withstand the harshest offshore environments. Belden's MarineTuff certified cables are highly reliable, rugged solutions that will function in a variety of challenging offshore activities: mobile drilling, fixed platform, floating production, storage and offloading (FPSO), marine vessels.

Oil and Gas platforms must continuously achieve optimal performance, while operating in harsh environments under mission-critical conditions. Demands on communication networks include safety, availability, reliability and durability in environments where vibration, corrosion, fluctuating temperature, splash water, and pollution occur. The MarineTuff instrumentation and control cables are designed to operate in these conditions.

The MarineTuff instrumentation and control line features 600V TC-ER rated multiconductor, paired, and triad cables. They feature XLP conductors appropriate for 90 degrees C wet/dry demands, class I and II / Division 2 hazardous location ratings, and HaloarrestXLink low smoke zero halogen jackets (LSZH).

Key Attributes

- Type P ratings on all jackets and options
- LSZH jackets on all cables and options
- Bronze braid options on all cables and options
- ABS certified, DNV (pending)
- 10 year warranty

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff UL Control Cable

600 V Type TC (or MC) Cables



Featured Options:

- Bronze Braid Armoring
- Continuous Aluminum Armor (ABS) - Type MC
- LSZH Thermoset Jacket (Standard)
- Type P Rated Jacket
- Sunlight and Oil Resistant

Construction:


1. LSZH Thermoset Jacket
2. XLP Insulation
3. Flexible Stranded Tinned Copper Conductors
4. Round and Smooth

NOTE: Also available on all options, bronze braid armor with LSZH second jacket or overall foil shield 100% coverage (not pictured).

Certifications/Compliance

- ABS (American Bureau of Shipping)
- DNV (Det Norske Veritas)* pending
- IEEE 45 Electrical Installation on Shipboard
- IEEE 1580 Type P jacketing (recommended practice for marine cables for use on shipboard in fixed or floating facilities)
- UL 1309 marine shipboard cables
- IEC 60811-2-1 compliant for hydrocarbon resistance
- IEC 60754-1 compliant jacket for halogen content
- IEC 60754-2 compliant jacket for acid gas emissions
- IEC 60092-350 electrical installations on ships)
- UL 1277 TC-ER crush and impact resistant (UL TC for 2-conductor cables)
- IEEE 1202 and FT4 flame-resistant
- IEC 60332-3-22

* excludes continuous armored constructions



MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 18 AWG, Unshielded, Thermoset Jacket

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm

18 AWG • Unshielded • Thermoset Jacket • Type TC

Flexible Stranded (16 x 30) TC Conductors • XLPE Insulation • LSZH Jacket									
27916Z	2	E2	44	3.20	81.3	.21 x 0.31	5.3 x 7.9	0.05	1.1
27325Z	2	E2	44	3.10	78.7	0.31	7.9	0.05	1.1
28334Z	3	E2	66	3.30	83.8	0.33	8.4	0.05	1.1
28326Z	4	E2	88	3.60	91.4	0.36	9.1	0.05	1.1
28335Z	5	E2	110	3.90	99.1	0.39	9.9	0.05	1.1
28600Z	6	E2	132	4.20	106.7	0.41	10.4	0.05	1.1
28327Z	7	E2	154	4.30	109.2	0.42	10.7	0.05	1.1
28601Z	8	E2	176	4.50	114.3	0.45	11.4	0.05	1.1
28336Z	9	E2	198	4.90	124.5	0.49	12.4	0.05	1.1
28328Z	10	E2	220	5.70	144.8	0.56	14.2	0.06	1.5
28602Z	11	E2	242	5.80	147.3	0.58	14.7	0.06	1.5
28329Z	12	E2	264	5.80	147.3	0.58	14.7	0.06	1.5
28603Z	13	E2	286	6.10	154.9	0.61	15.5	0.06	1.5
28604Z	14	E2	308	6.10	154.9	0.61	15.5	0.06	1.5
28605Z	15	E2	330	6.40	162.6	0.64	16.3	0.06	1.5
28606Z	16	E2	352	6.40	162.6	0.64	16.3	0.06	1.5
28607Z	17	E2	374	6.80	172.7	0.67	17.0	0.06	1.5
28608Z	18	E2	396	6.80	172.7	0.67	17.0	0.06	1.5
28609Z	19	E2	418	6.80	172.7	0.67	17.0	0.06	1.5
28610Z	20	E2	440	7.10	180.3	0.70	17.8	0.06	1.5
28611Z	25	E2	550	8.00	203.2	0.80	20.3	0.06	1.5
28612Z	30	E2	660	8.30	210.8	0.82	20.8	0.06	1.5
28613Z	37	E2	814	9.40	238.8	0.93	23.6	0.08	2.0
28614Z	50	E2	1100	10.90	276.9	1.09	27.7	0.08	2.0
28632Z	60	E2	1320	11.70	297.2	1.17	29.7	0.08	2.0

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

18 AWG • Unshielded • Thermoset Jacket • Bronze Braid Armor • Type TC (continued next page)

Flexible Stranded (16 x 30) TC Conductors • XLPE Insulation • LSZH Jacket											
Z27916Z	2	E2	44	4.13	105.0	0.45	8.7	0.05	1.1	0.06	1.4
Z27325Z	2	E2	44	5.45	105.0	0.45	8.7	0.05	1.1	0.06	1.4
Z28334Z	3	E2	66	5.69	111.1	0.47	9.3	0.05	1.1	0.06	1.4
Z28326Z	4	E2	88	6.05	120.2	0.50	10.0	0.05	1.1	0.06	1.4
Z28335Z	5	E2	110	6.41	129.4	0.53	10.8	0.05	1.1	0.06	1.4
Z28600Z	6	E2	132	6.86	140.7	0.57	11.7	0.05	1.1	0.06	1.4
Z28327Z	7	E2	154	6.98	143.8	0.58	12.0	0.05	1.1	0.06	1.4
Z28601Z	8	E2	176	7.34	152.9	0.61	12.7	0.05	1.1	0.06	1.4
Z28336Z	9	E2	198	7.82	165.1	0.65	13.8	0.05	1.1	0.06	1.4

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 18 AWG, Unshielded, Thermoset Jacket



Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

18 AWG • Unshielded • Thermoset Jacket • Bronze Braid Armor • Type TC (continued from previous page)

Flexible Stranded (16 x 30) TC Conductors • XLPE Insulation • LSZH Jacket											
Z28328Z	10	E2	220	8.66	186.4	0.72	15.5	0.06	1.5	0.06	1.4
Z28602Z	11	E2	242	8.90	192.5	0.74	16.0	0.06	1.5	0.06	1.4
Z28329Z	12	E2	264	8.90	192.5	0.74	16.0	0.06	1.5	0.06	1.4
Z28603Z	13	E2	286	9.26	201.7	0.77	16.8	0.06	1.5	0.06	1.4
Z28604Z	14	E2	308	9.26	201.7	0.77	16.8	0.06	1.5	0.06	1.4
Z28605Z	15	E2	330	9.62	210.8	0.80	17.6	0.06	1.5	0.06	1.4
Z28606Z	16	E2	352	9.62	210.8	0.80	17.6	0.06	1.5	0.06	1.4
Z28607Z	17	E2	374	9.98	220.0	0.83	18.3	0.06	1.5	0.06	1.4
Z28608Z	18	E2	396	9.98	220.0	0.83	18.3	0.06	1.5	0.06	1.4
Z28609Z	19	E2	418	9.98	220.0	0.83	18.3	0.06	1.5	0.06	1.4
Z28610Z	20	E2	440	10.34	229.1	0.86	19.1	0.06	1.5	0.06	1.4
Z28611Z	25	E2	550	11.54	259.6	0.96	21.6	0.06	1.5	0.06	1.4
Z28612Z	30	E2	660	11.78	265.7	0.98	22.1	0.06	1.5	0.06	1.4
Z28613Z	37	E2	814	13.10	299.2	1.09	24.9	0.08	2.0	0.06	1.4
Z28614Z	50	E2	1100	15.02	348.0	1.25	29.0	0.08	2.0	0.06	1.4
Z28632Z	60	E2	1320	15.98	372.4	1.33	31.0	0.08	2.0	0.06	1.4

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

18 AWG • Unshielded • Continuous Armor • Thermoset Jacket • Type MC (continued next page)

Flexible Stranded (16 x 30) TC Conductors • XLPE Insulation • LSZH Jacket											
NOTE: Continuous armor cables are not DNV rated											
W27916Z	2	E2	44	6.98	177.4	0.58	14.8	0.05	1.1	0.06	1.4
W27325Z	2	E2	44	6.98	177.4	0.58	14.8	0.05	1.1	0.06	1.4
W28334Z	3	E2	66	7.22	183.5	0.60	15.3	0.05	1.1	0.06	1.4
W28326Z	4	E2	88	7.58	192.6	0.63	16.1	0.05	1.1	0.06	1.4
W28335Z	5	E2	110	7.94	201.8	0.66	16.8	0.05	1.1	0.06	1.4
W28600Z	6	E2	132	8.18	207.9	0.68	17.3	0.05	1.1	0.06	1.4
W28327Z	7	E2	154	8.30	210.9	0.69	17.6	0.05	1.1	0.06	1.4
W28601Z	8	E2	176	8.66	220.1	0.72	18.3	0.05	1.1	0.06	1.4
W28336Z	9	E2	198	9.14	232.3	0.76	19.4	0.05	1.1	0.06	1.4
W28328Z	10	E2	220	9.98	253.6	0.83	21.1	0.06	1.5	0.06	1.4
W28602Z	11	E2	242	10.22	259.7	0.85	21.6	0.06	1.5	0.06	1.4
W28329Z	12	E2	264	10.22	259.7	0.85	21.6	0.06	1.5	0.06	1.4
W28603Z	13	E2	286	10.58	268.8	0.88	22.4	0.06	1.5	0.06	1.4
W28604Z	14	E2	308	10.58	268.8	0.88	22.4	0.06	1.5	0.06	1.4
W28605Z	15	E2	330	10.94	278.0	0.91	23.2	0.06	1.5	0.06	1.4
W28606Z	16	E2	352	10.94	278.0	0.91	23.2	0.06	1.5	0.06	1.4
W28607Z	17	E2	374	11.30	287.1	0.94	23.9	0.06	1.5	0.06	1.4

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 18 AWG, Unshielded and Shielded, Thermoset Jacket

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

18 AWG • Unshielded • Continuous Armor • Thermoset Jacket • Type MC (continued from previous page)

Flexible Stranded (16 x 30) TC Conductors • XLPE Insulation • LSZH Jacket <small>NOTE: Continuous armor cables are not DNV rated</small>											
W28608Z	18	E2	396	11.30	287.1	0.94	23.9	0.06	1.5	0.06	1.4
W28609Z	19	E2	418	11.30	287.1	0.94	23.9	0.06	1.5	0.06	1.4
W28610Z	20	E2	440	11.66	296.3	0.97	24.7	0.06	1.5	0.06	1.4
W28611Z	25	E2	550	12.86	326.7	1.07	27.2	0.06	1.5	0.06	1.4
W28612Z	30	E2	660	13.10	332.8	1.09	27.7	0.06	1.5	0.06	1.4
W28613Z	37	E2	814	14.42	366.4	1.20	30.5	0.08	2.0	0.06	1.4
W28614Z	50	E2	1100	16.46	418.2	1.37	34.8	0.08	2.0	0.06	1.5
W28632Z	60	E2	1320	17.42	442.6	1.45	36.9	0.08	2.0	0.06	1.5

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm

18 AWG • Shielded 100%, Beldfoil • Thermoset Jacket • Type TC

Flexible Stranded (16 x 30) TC Conductors • XLPE Insulation • LSZH Jacket									
27325ZS	2	E2	67	3.13	79.5	0.31	8.0	0.05	1.1
28334ZS	3	E2	90	3.33	84.6	0.33	8.5	0.05	1.1
28326ZS	4	E2	112	3.63	92.2	0.36	9.2	0.05	1.1

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 16 AWG, Unshielded, Thermoset Jacket



Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm

16 AWG • Unshielded • Thermoset Jacket • Type TC

Flexible Stranded (26 x 30) TC Conductors • XLPE Insulation • LSZH Jacket									
27917Z	2	E2	44	3.30	83.8	.212 x .330	5.38 x 8.38	0.05	1.1
27337Z	2	E2	44	3.50	88.9	0.34	8.6	0.05	1.1
28331Z	3	E2	66	3.60	91.4	0.35	8.9	0.05	1.1
28338Z	4	E2	88	3.90	99.1	0.39	9.9	0.05	1.1
28339Z	5	E2	110	4.30	109.2	0.42	10.7	0.05	1.1
28615Z	6	E2	132	4.60	116.8	0.46	11.7	0.05	1.1
28323Z	7	E2	154	4.60	116.8	0.46	11.7	0.05	1.1
28616Z	8	E2	176	5.00	127.0	0.49	12.4	0.05	1.1
28340Z	9	E2	198	5.70	144.8	0.56	14.2	0.05	1.1
28617Z	10	E2	220	6.10	154.9	0.61	15.5	0.05	1.1
28618Z	11	E2	242	6.30	160.0	0.63	16.0	0.05	1.1
28341Z	12	E2	264	6.30	160.0	0.63	16.0	0.05	1.1
28619Z	13	E2	286	6.60	167.6	0.66	16.8	0.05	1.1
28620Z	14	E2	308	6.60	167.6	0.66	16.8	0.05	1.1
28621Z	15	E2	330	7.00	177.8	0.69	17.5	0.06	1.5
28330Z	16	E2	352	7.00	177.8	0.69	17.5	0.06	1.5
28622Z	17	E2	374	7.40	188.0	0.73	18.5	0.06	1.5
28623Z	18	E2	396	7.40	188.0	0.73	18.5	0.06	1.5
28624Z	19	E2	418	7.40	188.0	0.73	18.5	0.06	1.5
28625Z	20	E2	440	7.70	195.6	0.77	19.6	0.06	1.5
28324Z	25	E2	550	9.20	233.7	0.91	23.1	0.08	2.0
28626Z	30	E2	660	9.50	241.3	0.95	24.1	0.08	2.0
28627Z	37	E2	814	10.20	259.1	1.02	25.9	0.08	2.0
28628Z	50	E2	1100	11.90	302.3	1.19	30.2	0.08	2.0

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

16 AWG • Unshielded • Thermoset Jacket • Bronze Braid Armor • Type TC (continued next page)

Flexible Stranded (26 x 30) TC Conductors • XLPE Insulation • LSZH Jacket											
Z27917Z	2	E2	44	5.69	144.6	0.47	12.0	0.05	1.1	0.06	1.4
Z27337Z	2	E2	44	5.81	147.7	0.48	12.3	0.05	1.1	0.06	1.4
Z28331Z	3	E2	66	5.93	150.7	0.49	12.6	0.05	1.1	0.06	1.4
Z28338Z	4	E2	88	6.41	162.9	0.53	13.6	0.05	1.1	0.06	1.4
Z28339Z	5	E2	110	6.98	177.3	0.58	14.8	0.05	1.1	0.06	1.4
Z28615Z	6	E2	132	7.46	189.5	0.62	15.8	0.05	1.1	0.06	1.4
Z28323Z	7	E2	154	7.46	189.5	0.62	15.8	0.05	1.1	0.06	1.4
Z28616Z	8	E2	176	7.82	198.6	0.65	16.6	0.05	1.1	0.06	1.4
Z28340Z	9	E2	198	8.66	220.0	0.72	18.3	0.05	1.1	0.06	1.4
Z28617Z	10	E2	220	9.26	235.2	0.77	19.6	0.05	1.1	0.06	1.4

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 16 AWG, Unshielded, Thermoset Jacket

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

16 AWG • Unshielded • Thermoset Jacket • Bronze Braid Armor • Type TC (continued from previous page)

Flexible Stranded (26 x 30) TC Conductors • XLPE Insulation • LSZH Jacket											
Z28618Z	11	E2	242	9.50	241.3	0.79	20.1	0.05	1.1	0.06	1.4
Z28341Z	12	E2	264	9.50	241.3	0.79	20.1	0.05	1.1	0.06	1.4
Z28619Z	13	E2	286	9.86	250.4	0.82	20.9	0.05	1.1	0.06	1.4
Z28620Z	14	E2	308	9.86	250.4	0.82	20.9	0.05	1.1	0.06	1.4
Z28621Z	15	E2	330	10.22	259.6	0.85	21.6	0.06	1.5	0.06	1.4
Z28330Z	16	E2	352	10.22	259.6	0.85	21.6	0.06	1.5	0.06	1.4
Z28622Z	17	E2	374	10.70	271.8	0.89	22.6	0.06	1.5	0.06	1.4
Z28623Z	18	E2	396	10.70	271.8	0.89	22.6	0.06	1.5	0.06	1.4
Z28624Z	19	E2	418	10.70	271.8	0.89	22.6	0.06	1.5	0.06	1.4
Z28625Z	20	E2	440	11.18	284.0	0.93	23.7	0.06	1.5	0.06	1.4
Z28324Z	25	E2	550	12.86	326.6	1.07	27.2	0.08	2.0	0.06	1.4
Z28626Z	30	E2	660	13.34	338.8	1.11	28.2	0.08	2.0	0.06	1.4
Z28627Z	37	E2	814	14.18	360.2	1.18	30.0	0.08	2.0	0.06	1.4
Z28628Z	50	E2	1100	16.55	420.3	1.38	35.0	0.08	2.0	0.06	1.5

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

16 AWG • Unshielded • Continuous Armor • Thermoset Jacket • Type MC (continued next page)

Flexible Stranded (26 x 30) TC Conductors • XLPE Insulation • LSZH Jacket											
NOTE: Continuous armor cables are not DNV rated											
W27917Z	2	E2	44	7.22	183.5	0.60	15.3	0.05	1.1	0.06	1.4
W27337Z	2	E2	44	7.34	186.5	0.61	15.5	0.05	1.1	0.06	1.4
W28331Z	3	E2	66	7.46	189.6	0.62	15.8	0.05	1.1	0.06	1.4
W28338Z	4	E2	88	7.94	201.8	0.66	16.8	0.05	1.1	0.06	1.4
W28339Z	5	E2	110	8.30	210.9	0.69	17.6	0.05	1.1	0.06	1.4
W28615Z	6	E2	132	8.78	223.1	0.73	18.6	0.05	1.1	0.06	1.4
W28323Z	7	E2	154	8.78	223.1	0.73	18.6	0.05	1.1	0.06	1.4
W28616Z	8	E2	176	9.14	232.3	0.76	19.4	0.05	1.1	0.06	1.4
W28340Z	9	E2	198	9.98	253.6	0.83	21.1	0.05	1.1	0.06	1.4
W28617Z	10	E2	220	10.58	268.8	0.88	22.4	0.05	1.1	0.06	1.4
W28618Z	11	E2	242	10.82	274.9	0.90	22.9	0.05	1.1	0.06	1.4
W28341Z	12	E2	264	10.82	274.9	0.90	22.9	0.05	1.1	0.06	1.4
W28619Z	13	E2	286	11.18	284.1	0.93	23.7	0.05	1.1	0.06	1.4
W28620Z	14	E2	308	11.18	284.1	0.93	23.7	0.05	1.1	0.06	1.4
W28621Z	15	E2	330	11.54	293.2	0.96	24.4	0.06	1.5	0.06	1.4
W28330Z	16	E2	352	11.54	293.2	0.96	24.4	0.06	1.5	0.06	1.4
W28622Z	17	E2	374	12.02	305.4	1.00	25.5	0.06	1.5	0.06	1.4
W28623Z	18	E2	396	12.02	305.4	1.00	25.5	0.06	1.5	0.06	1.4
W28624Z	19	E2	418	12.02	305.4	1.00	25.5	0.06	1.5	0.06	1.4
W28625Z	20	E2	440	12.50	317.6	1.04	26.5	0.06	1.5	0.06	1.4

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 16 AWG, Unshielded and Shielded, Thermoset Jacket

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

16 AWG • Unshielded • Continuous Armor • Thermoset Jacket • Type MC (continued from previous page)

Flexible Stranded (26 x 30) TC Conductors • XLPE Insulation • LSZH Jacket <small>NOTE: Continuous armor cables are not DNV rated</small>											
W28324Z	25	E2	550	14.18	360.3	1.18	30.0	0.08	2.0	0.06	1.4
W28626Z	30	E2	660	14.66	372.5	1.22	31.0	0.08	2.0	0.06	1.4
W28627Z	37	E2	814	15.50	393.8	1.29	32.8	0.08	2.0	0.06	1.4
W28628Z	50	E2	1100	17.66	448.7	1.47	37.4	0.08	2.0	0.06	1.5

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm

16 AWG • Shielded 100%, Beldfoil • Thermoset Jacket • Type TC

Flexible Stranded (26 x 30) TC Conductors • XLPE Insulation • LSZH Jacket									
27337ZS	2	E2	94	3.43	87.1	0.34	8.7	0.05	1.1
28331ZS	3	E2	130	3.53	89.7	0.35	9.0	0.05	1.1

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 14 AWG, Unshielded, Thermoset Jacket



Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm
14 AWG • Unshielded • Thermoset Jacket • Type TC									
Flexible Stranded (41 x 30) TC Conductors • XLPE Insulation • LSZH Jacket									
27080Z	2	E2	108	3.70	94.0	.24 x .37	6.1 x 9.4	0.05	1.1
27636Z	2	E2	108	3.70	94.0	0.36	9.1	0.05	1.1
28081Z	3	E2	162	3.80	96.5	0.38	9.7	0.05	1.1
28082Z	4	E2	216	4.20	106.7	0.42	10.7	0.05	1.1
28083Z	5	E2	270	4.60	116.8	0.45	11.4	0.05	1.1
28084Z	6	E2	324	5.00	127.0	0.50	12.7	0.05	1.1
28085Z	7	E2	378	5.00	127.0	0.50	12.7	0.05	1.1
28086Z	8	E2	432	5.70	144.8	0.57	14.5	0.05	1.1
28087Z	9	E2	486	6.20	157.5	0.62	15.7	0.05	1.1
28088Z	10	E2	540	6.70	170.2	0.66	16.8	0.06	1.5
28089Z	11	E2	594	6.90	175.3	0.68	17.3	0.06	1.5
28090Z	12	E2	648	6.90	175.3	0.68	17.3	0.06	1.5
28091Z	13	E2	702	7.20	182.9	0.72	18.3	0.06	1.5
28092Z	14	E2	756	7.20	182.9	0.72	18.3	0.06	1.5
28093Z	15	E2	810	7.60	193.0	0.76	19.3	0.06	1.5
28094Z	16	E2	864	7.60	193.0	0.76	19.3	0.06	1.5
28095Z	17	E2	918	8.00	203.2	0.80	20.3	0.06	1.5
28096Z	18	E2	972	8.00	203.2	0.80	20.3	0.06	1.5
28097Z	19	E2	1026	8.00	203.2	0.80	20.3	0.06	1.5
28098Z	20	E2	1080	8.90	226.1	0.88	22.4	0.06	1.5
28099Z	21	E2	1134	8.90	226.1	0.88	22.4	0.06	1.5
28100Z	22	E2	1188	9.30	236.2	0.92	23.4	0.06	1.5
28101Z	23	E2	1242	9.30	236.2	0.92	23.4	0.06	1.5
28102Z	24	E2	1296	9.80	248.9	0.97	24.6	0.06	1.5
28103Z	25	E2	1350	10.00	254.0	0.99	25.1	0.06	1.5
28104Z	26	E2	1404	10.00	254.0	0.99	25.1	0.06	1.5
28105Z	27	E2	1458	10.00	254.0	0.99	25.1	0.08	2.0
28106Z	28	E2	1512	10.30	261.6	1.03	26.2	0.08	2.0
28107Z	29	E2	1566	10.30	261.6	1.03	26.2	0.08	2.0
28108Z	30	E2	1620	10.30	261.6	1.03	26.2	0.08	2.0
28629Z	37	E2	1998	11.10	281.9	1.11	28.2	0.08	2.0
28912Z	50	E2	2700	13.00	330.2	1.30	33.0	0.08	2.0

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 14 AWG, Unshielded, Thermoset Jacket



Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

14 AWG • Unshielded • Thermoset Jacket • Bronze Braid Armor • Type TC

Flexible Stranded (41 x 30) TC Conductors • XLPE Insulation • LSZH Jacket											
Z27080Z	2	E2	108	6.17	156.8	0.51	13.1	0.05	1.1	0.06	1.4
Z27636Z	2	E2	108	6.05	153.8	0.50	12.8	0.05	1.1	0.06	1.4
Z28081Z	3	E2	162	6.29	159.9	0.52	13.3	0.05	1.1	0.06	1.4
Z28082Z	4	E2	216	6.98	177.3	0.58	14.8	0.05	1.1	0.06	1.4
Z28083Z	5	E2	270	7.34	186.4	0.61	15.5	0.05	1.1	0.06	1.4
Z28084Z	6	E2	324	7.94	201.7	0.66	16.8	0.05	1.1	0.06	1.4
Z28085Z	7	E2	378	7.94	201.7	0.66	16.8	0.05	1.1	0.06	1.4
Z28086Z	8	E2	432	8.78	223.0	0.73	18.6	0.05	1.1	0.06	1.4
Z28087Z	9	E2	486	9.38	238.3	0.78	19.9	0.05	1.1	0.06	1.4
Z28088Z	10	E2	540	9.86	250.4	0.82	20.9	0.06	1.5	0.06	1.4
Z28089Z	11	E2	594	10.10	256.5	0.84	21.4	0.06	1.5	0.06	1.4
Z28090Z	12	E2	648	10.10	256.5	0.84	21.4	0.06	1.5	0.06	1.4
Z28091Z	13	E2	702	10.58	268.7	0.88	22.4	0.06	1.5	0.06	1.4
Z28092Z	14	E2	756	10.58	268.7	0.88	22.4	0.06	1.5	0.06	1.4
Z28093Z	15	E2	810	11.06	280.9	0.92	23.4	0.06	1.5	0.06	1.4
Z28094Z	16	E2	864	11.06	280.9	0.92	23.4	0.06	1.5	0.06	1.4
Z28095Z	17	E2	918	11.54	293.1	0.96	24.4	0.06	1.5	0.06	1.4
Z28096Z	18	E2	972	11.54	293.1	0.96	24.4	0.06	1.5	0.06	1.4
Z28097Z	19	E2	1026	11.54	293.1	0.96	24.4	0.06	1.5	0.06	1.4
Z28098Z	20	E2	1080	12.50	317.5	1.04	26.5	0.06	1.5	0.06	1.4
Z28099Z	21	E2	1134	12.50	317.5	1.04	26.5	0.06	1.5	0.06	1.4
Z28100Z	22	E2	1188	12.98	329.7	1.08	27.5	0.06	1.5	0.06	1.4
Z28101Z	23	E2	1242	12.98	329.7	1.08	27.5	0.06	1.5	0.06	1.4
Z28102Z	24	E2	1296	13.58	344.9	1.13	28.7	0.06	1.5	0.06	1.4
Z28103Z	25	E2	1350	13.82	351.0	1.15	29.3	0.06	1.5	0.06	1.4
Z28104Z	26	E2	1404	13.82	351.0	1.15	29.3	0.06	1.5	0.06	1.4
Z28105Z	27	E2	1458	13.82	351.0	1.15	29.3	0.08	2.0	0.06	1.4
Z28106Z	28	E2	1512	14.30	363.2	1.19	30.3	0.08	2.0	0.06	1.4
Z28107Z	29	E2	1566	14.30	363.2	1.19	30.3	0.08	2.0	0.06	1.4
Z28108Z	30	E2	1620	14.30	363.2	1.19	30.3	0.08	2.0	0.06	1.4
Z28629Z	37	E2	1998	15.26	387.6	1.27	32.3	0.08	2.0	0.06	1.4
Z28912Z	50	E2	2700	17.87	453.8	1.49	37.8	0.08	2.0	0.06	1.5

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 14 AWG, Unshielded and Unshielded, Thermoset Jacket

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

14 AWG • Unshielded • Continuous Armor • Thermoset Jacket • Type MC

Flexible Stranded (41 x 30) TC Conductors • XLPE Insulation • LSZH Jacket				NOTE: Continuous armor cables are not DNV rated							
W27080Z	2	E2	108	7.70	195.7	0.64	16.3	0.05	1.1	0.06	1.4
W27636Z	2	E2	108	7.58	192.6	0.63	16.1	0.05	1.1	0.06	1.4
W28081Z	3	E2	162	7.82	198.7	0.65	16.6	0.05	1.1	0.06	1.4
W28082Z	4	E2	216	8.30	210.9	0.69	17.6	0.05	1.1	0.06	1.4
W28083Z	5	E2	270	8.66	220.1	0.72	18.3	0.05	1.1	0.06	1.4
W28084Z	6	E2	324	9.26	235.3	0.77	19.6	0.05	1.1	0.06	1.4
W28085Z	7	E2	378	9.26	235.3	0.77	19.6	0.05	1.1	0.06	1.4
W28086Z	8	E2	432	10.10	256.6	0.84	21.4	0.05	1.1	0.06	1.4
W28087Z	9	E2	486	10.70	271.9	0.89	22.7	0.05	1.1	0.06	1.4
W28088Z	10	E2	540	11.18	284.1	0.93	23.7	0.06	1.5	0.06	1.4
W28089Z	11	E2	594	11.42	290.2	0.95	24.2	0.06	1.5	0.06	1.4
W28090Z	12	E2	648	11.42	290.2	0.95	24.2	0.06	1.5	0.06	1.4
W28091Z	13	E2	702	11.90	302.4	0.99	25.2	0.06	1.5	0.06	1.4
W28092Z	14	E2	756	11.90	302.4	0.99	25.2	0.06	1.5	0.06	1.4
W28093Z	15	E2	810	12.38	314.6	1.03	26.2	0.06	1.5	0.06	1.4
W28094Z	16	E2	864	12.38	314.6	1.03	26.2	0.06	1.5	0.06	1.4
W28095Z	17	E2	918	12.86	326.7	1.07	27.2	0.06	1.5	0.06	1.4
W28096Z	18	E2	972	12.86	326.7	1.07	27.2	0.06	1.5	0.06	1.4
W28097Z	19	E2	1026	12.86	326.7	1.07	27.2	0.06	1.5	0.06	1.4
W28098Z	20	E2	1080	13.82	351.1	1.15	29.3	0.06	1.5	0.06	1.4
W28099Z	21	E2	1134	13.82	351.1	1.15	29.3	0.06	1.5	0.06	1.4
W28100Z	22	E2	1188	14.30	363.3	1.19	30.3	0.06	1.5	0.06	1.4
W28101Z	23	E2	1242	14.30	363.3	1.19	30.3	0.06	1.5	0.06	1.4
W28102Z	24	E2	1296	14.90	378.6	1.24	31.5	0.06	1.5	0.06	1.4
W28103Z	25	E2	1350	15.14	384.7	1.26	32.1	0.06	1.5	0.06	1.4
W28104Z	26	E2	1404	15.14	384.7	1.26	32.1	0.06	1.5	0.06	1.4
W28105Z	27	E2	1458	15.14	384.7	1.26	32.1	0.08	2.0	0.06	1.4
W28106Z	28	E2	1512	15.62	396.8	1.30	33.1	0.08	2.0	0.06	1.4
W28107Z	29	E2	1566	15.62	396.8	1.30	33.1	0.08	2.0	0.06	1.4
W28108Z	30	E2	1620	15.62	396.8	1.30	33.1	0.08	2.0	0.06	1.4
W28629Z	37	E2	1998	16.70	424.3	1.39	35.4	0.08	2.0	0.06	1.5
W28912Z	50	E2	2700	18.98	482.2	1.58	40.2	0.08	2.0	0.06	1.5

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm

14 AWG • Shielded 100%, Beldfoil • Thermoset Jacket • Type TC

Flexible Stranded (41 x 30) TC Conductors • XLPE Insulation • LSZH Jacket									
28081ZS	3	E2	99	3.83	97.3	0.38	9.7	0.05	1.1
28082ZS	4	E2	273	4.23	107.4	0.42	10.7	0.05	1.1

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 12 AWG, Unshielded, Thermoset Jacket

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm

12 AWG • Unshielded • Thermoset Jacket • Type TC

Flexible Stranded (65 x 30) TC Conductors • XLPE Insulation • LSZH Jacket									
27109Z	2	E2	172	4.10	104.1	0.40	10.2	0.05	1.1
27641Z	2	E2	172	4.10	104.1	0.40	10.2	0.05	1.1
28110Z	3	E2	258	4.20	106.7	0.42	10.7	0.05	1.1
28111Z	4	E2	344	4.60	116.8	0.46	11.7	0.05	1.1
28112Z	5	E2	430	5.00	127.0	0.50	12.7	0.05	1.1
28113Z	6	E2	516	6.00	152.4	0.59	15.0	0.05	1.1
28114Z	7	E2	602	6.00	152.4	0.59	15.0	0.05	1.1
28115Z	8	E2	688	6.40	162.6	0.64	16.3	0.06	1.5
28116Z	9	E2	774	6.90	175.3	0.69	17.5	0.06	1.5
28117Z	10	E2	860	7.50	190.5	0.75	19.1	0.06	1.5
28118Z	11	E2	946	7.70	195.6	0.77	19.6	0.06	1.5
28119Z	12	E2	1032	7.70	195.6	0.77	19.6	0.06	1.5
28120Z	13	E2	1118	8.10	205.7	0.81	20.6	0.06	1.5
28121Z	14	E2	1204	8.20	208.3	0.81	20.6	0.06	1.5
28122Z	15	E2	1290	9.00	228.6	0.90	22.9	0.06	1.5
28123Z	16	E2	1376	9.00	228.6	0.90	22.9	0.06	1.5
28124Z	17	E2	1462	9.50	241.3	0.95	24.1	0.06	1.5
28125Z	18	E2	1548	9.50	241.3	0.95	24.1	0.06	1.5
28126Z	19	E2	1634	9.50	241.3	0.95	24.1	0.06	1.5
28127Z	20	E2	1720	10.00	254.0	0.99	25.1	0.08	2.0
28128Z	21	E2	1806	10.00	254.0	0.99	25.1	0.08	2.0
28129Z	22	E2	1892	10.50	266.7	1.04	26.4	0.08	2.0
28130Z	23	E2	1978	10.50	266.7	1.04	26.4	0.08	2.0
28131Z	24	E2	2064	11.00	279.4	1.10	27.9	0.08	2.0
28132Z	25	E2	2150	11.30	287.0	1.12	28.4	0.08	2.0
28133Z	26	E2	2236	11.30	287.0	1.12	28.4	0.08	2.0
28134Z	27	E2	2322	11.30	287.0	1.12	28.4	0.08	2.0
28135Z	28	E2	2408	11.70	297.2	1.16	29.5	0.08	2.0
28136Z	29	E2	2494	11.70	297.2	1.16	29.5	0.08	2.0
28137Z	30	E2	2580	11.70	297.2	1.16	29.5	0.08	2.0
28630Z	37	E2	3182	12.60	320.0	1.26	32.0	0.08	2.0
28634Z	50	E2	4300	14.80	375.9	1.47	37.3	0.08	2.0

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 12 AWG, Unshielded, Thermoset Jacket



Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm
12 AWG • Unshielded • Thermoset Jacket • Bronze Braid Armor • Type TC											
Flexible Stranded (65 x 30) TC Conductors • XLPE Insulation • LSZH Jacket											
Z27109Z	2	E2	172	6.64	171.2	0.55	14.3	0.05	1.1	0.06	1.4
Z27641Z	2	E2	172	6.64	171.2	0.55	14.3	0.05	1.1	0.06	1.4
Z28110Z	3	E2	258	6.87	177.3	0.57	14.8	0.05	1.1	0.06	1.4
Z28111Z	4	E2	344	7.34	189.5	0.61	15.8	0.05	1.1	0.06	1.4
Z28112Z	5	E2	430	7.82	201.7	0.65	16.8	0.05	1.1	0.06	1.4
Z28113Z	6	E2	516	8.88	229.1	0.74	19.1	0.05	1.1	0.06	1.4
Z28114Z	7	E2	602	8.88	229.1	0.74	19.1	0.05	1.1	0.06	1.4
Z28115Z	8	E2	688	9.47	244.4	0.79	20.4	0.06	1.5	0.06	1.4
Z28116Z	9	E2	774	10.06	259.6	0.84	21.6	0.06	1.5	0.06	1.4
Z28117Z	10	E2	860	10.77	277.9	0.90	23.2	0.06	1.5	0.06	1.4
Z28118Z	11	E2	946	11.01	284.0	0.92	23.7	0.06	1.5	0.06	1.4
Z28119Z	12	E2	1032	11.01	284.0	0.92	23.7	0.06	1.5	0.06	1.4
Z28120Z	13	E2	1118	11.48	296.2	0.96	24.7	0.06	1.5	0.06	1.4
Z28121Z	14	E2	1204	11.48	296.2	0.96	24.7	0.06	1.5	0.06	1.4
Z28122Z	15	E2	1290	12.54	323.6	1.05	27.0	0.06	1.5	0.06	1.4
Z28123Z	16	E2	1376	12.54	323.6	1.05	27.0	0.06	1.5	0.06	1.4
Z28124Z	17	E2	1462	13.13	338.8	1.09	28.2	0.06	1.5	0.06	1.4
Z28125Z	18	E2	1548	13.13	338.8	1.09	28.2	0.06	1.5	0.06	1.4
Z28126Z	19	E2	1634	13.13	338.8	1.09	28.2	0.06	1.5	0.06	1.4
Z28127Z	20	E2	1720	13.61	351.0	1.13	29.3	0.08	2.0	0.06	1.4
Z28128Z	21	E2	1806	13.61	351.0	1.13	29.3	0.08	2.0	0.06	1.4
Z28129Z	22	E2	1892	14.20	366.3	1.18	30.5	0.08	2.0	0.06	1.4
Z28130Z	23	E2	1978	14.20	366.3	1.18	30.5	0.08	2.0	0.06	1.4
Z28131Z	24	E2	2064	14.91	384.6	1.24	32.0	0.08	2.0	0.06	1.4
Z28132Z	25	E2	2150	15.14	390.7	1.26	32.6	0.08	2.0	0.06	1.4
Z28133Z	26	E2	2236	15.14	390.7	1.26	32.6	0.08	2.0	0.06	1.4
Z28134Z	27	E2	2322	15.14	390.7	1.26	32.6	0.08	2.0	0.06	1.4
Z28135Z	28	E2	2408	15.61	402.8	1.30	33.6	0.08	2.0	0.06	1.4
Z28136Z	29	E2	2494	15.61	402.8	1.30	33.6	0.08	2.0	0.06	1.4
Z28137Z	30	E2	2580	15.61	402.8	1.30	33.6	0.08	2.0	0.06	1.4
Z28630Z	37	E2	3182	17.12	441.6	1.43	36.8	0.08	2.0	0.06	1.5
Z28634Z	50	E2	4300	19.72	508.7	1.64	42.4	0.08	2.0	0.07	1.7

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 12 AWG, Unshielded, Thermoset Jacket



Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

12 AWG • Unshielded • Continuous Armor • Thermoset Jacket • Type MC

Flexible Stranded (65 x 30) TC Conductors • XLPE Insulation • LSZH Jacket					NOTE: Continuous armor cables are not DNV rated						
W27109Z	2	E2	172	8.06	204.8	0.67	17.1	0.05	1.1	0.06	1.4
W27641Z	2	E2	172	8.06	204.8	0.67	17.1	0.05	1.1	0.06	1.4
W28110Z	3	E2	258	8.30	210.9	0.69	17.6	0.05	1.1	0.06	1.4
W28111Z	4	E2	344	8.78	223.1	0.73	18.6	0.05	1.1	0.06	1.4
W28112Z	5	E2	430	9.26	235.3	0.77	19.6	0.05	1.1	0.06	1.4
W28113Z	6	E2	516	10.34	262.7	0.86	21.9	0.05	1.1	0.06	1.4
W28114Z	7	E2	602	10.34	262.7	0.86	21.9	0.05	1.1	0.06	1.4
W28115Z	8	E2	688	10.94	278.0	0.91	23.2	0.06	1.5	0.06	1.4
W28116Z	9	E2	774	11.54	293.2	0.96	24.4	0.06	1.5	0.06	1.4
W28117Z	10	E2	860	12.26	311.5	1.02	26.0	0.06	1.5	0.06	1.4
W28118Z	11	E2	946	12.50	317.6	1.04	26.5	0.06	1.5	0.06	1.4
W28119Z	12	E2	1032	12.50	317.6	1.04	26.5	0.06	1.5	0.06	1.4
W28120Z	13	E2	1118	12.98	329.8	1.08	27.5	0.06	1.5	0.06	1.4
W28121Z	14	E2	1204	12.98	329.8	1.08	27.5	0.06	1.5	0.06	1.4
W28122Z	15	E2	1290	14.06	357.2	1.17	29.8	0.06	1.5	0.06	1.4
W28123Z	16	E2	1376	14.06	357.2	1.17	29.8	0.06	1.5	0.06	1.4
W28124Z	17	E2	1462	14.66	372.5	1.22	31.0	0.06	1.5	0.06	1.4
W28125Z	18	E2	1548	14.66	372.5	1.22	31.0	0.06	1.5	0.06	1.4
W28126Z	19	E2	1634	14.66	372.5	1.22	31.0	0.06	1.5	0.06	1.4
W28127Z	20	E2	1720	15.14	384.7	1.26	32.1	0.08	2.0	0.06	1.4
W28128Z	21	E2	1806	15.14	384.7	1.26	32.1	0.08	2.0	0.06	1.4
W28129Z	22	E2	1892	15.74	399.9	1.31	33.3	0.08	2.0	0.06	1.4
W28130Z	23	E2	1978	15.74	399.9	1.31	33.3	0.08	2.0	0.06	1.4
W28131Z	24	E2	2064	16.46	418.2	1.37	34.8	0.08	2.0	0.06	1.4
W28132Z	25	E2	2150	16.70	424.3	1.39	35.4	0.08	2.0	0.06	1.4
W28133Z	26	E2	2236	16.70	424.3	1.39	35.4	0.08	2.0	0.06	1.4
W28134Z	27	E2	2322	16.70	424.3	1.39	35.4	0.08	2.0	0.06	1.4
W28135Z	28	E2	2408	17.18	436.5	1.43	36.4	0.08	2.0	0.06	1.4
W28136Z	29	E2	2494	17.18	436.5	1.43	36.4	0.08	2.0	0.06	1.4
W28137Z	30	E2	2580	17.18	436.5	1.43	36.4	0.08	2.0	0.06	1.4
W28630Z	37	E2	3182	18.50	470.0	1.54	39.2	0.08	2.0	0.06	1.5
W28634Z	50	E2	4300	21.14	537.1	1.76	44.8	0.08	2.0	0.07	1.7

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 10 AWG, Unshielded, Thermoset Jacket



Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm

10 AWG • Unshielded • Thermoset Jacket • Type TC

Flexible Stranded (105 x 30) TC Conductors • XLPE Insulation • LSZH Jacket									
27138Z	2	E2	296	4.50	114.3	0.44	11.2	0.045	1.14
27643Z	2	E2	296	4.50	114.3	0.44	11.2	0.045	1.14
28139Z	3	E2	444	4.70	119.38	0.47	11.9	0.045	1.14
28140Z	4	E2	592	5.20	132.08	0.51	13.0	0.045	1.14
28141Z	5	E2	740	6.00	152.4	0.60	15.2	0.06	1.52
28142Z	6	E2	888	6.60	167.64	0.65	16.5	0.06	1.52
28143Z	7	E2	1036	6.60	167.64	0.65	16.5	0.06	1.52
28144Z	8	E2	1184	7.10	180.34	0.71	18.0	0.06	1.52
28145Z	9	E2	1332	7.60	193.04	0.76	19.3	0.06	1.52
28146Z	10	E2	1480	8.70	220.98	0.87	22.1	0.06	1.52
28147Z	11	E2	1628	9.00	228.6	0.90	22.9	0.06	1.52
28148Z	12	E2	1776	9.00	228.6	0.90	22.9	0.08	2.03

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

10 AWG • Unshielded • Thermoset Jacket • Bronze Braid Armor • Type TC

Flexible Stranded (105 x 30) TC Conductors • XLPE Insulation • LSZH Jacket											
Z27138Z	2	E2	296	7.22	183.4	0.60	15.3	0.045	1.14	0.06	1.4
Z27643Z	2	E2	296	7.22	183.4	0.60	15.3	0.045	1.14	0.06	1.4
Z28139Z	3	E2	444	7.58	192.5	0.63	16.0	0.045	1.14	0.06	1.4
Z28140Z	4	E2	592	8.06	204.7	0.67	17.1	0.045	1.14	0.06	1.4
Z28141Z	5	E2	740	9.14	232.2	0.76	19.3	0.06	1.52	0.06	1.4
Z28142Z	6	E2	888	9.74	247.4	0.81	20.6	0.06	1.52	0.06	1.4
Z28143Z	7	E2	1036	9.74	247.4	0.81	20.6	0.06	1.52	0.06	1.4
Z28144Z	8	E2	1184	10.46	265.7	0.87	22.1	0.06	1.52	0.06	1.4
Z28145Z	9	E2	1332	11.06	280.9	0.92	23.4	0.06	1.52	0.06	1.4
Z28146Z	10	E2	1480	12.38	314.5	1.03	26.2	0.06	1.52	0.06	1.4
Z28147Z	11	E2	1628	12.74	323.6	1.06	27.0	0.06	1.52	0.06	1.4
Z28148Z	12	E2	1776	12.74	323.6	1.06	27.0	0.08	2.03	0.06	1.4

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 10 AWG, Unshielded, Thermoset Jacket



Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

10 AWG • Unshielded • Continuous Armor • Thermoset Jacket • Type MC

Flexible Stranded (105 x 30) TC Conductors • XLPE Insulation • LSZH Jacket <small>NOTE: Continuous armor cables are not DNV rated</small>											
W27138Z	2	E2	296	8.54	217.0	0.71	18.1	0.045	1.14	0.06	1.4
W27643Z	2	E2	296	8.54	217.0	0.71	18.1	0.045	1.14	0.06	1.4
W28139Z	3	E2	444	8.90	226.2	0.74	18.8	0.045	1.14	0.06	1.4
W28140Z	4	E2	592	9.38	238.4	0.78	19.9	0.045	1.14	0.06	1.4
W28141Z	5	E2	740	10.46	265.8	0.87	22.1	0.06	1.52	0.06	1.4
W28142Z	6	E2	888	11.06	281.0	0.92	23.4	0.06	1.52	0.06	1.4
W28143Z	7	E2	1036	11.06	281.0	0.92	23.4	0.06	1.52	0.06	1.4
W28144Z	8	E2	1184	11.78	299.3	0.98	24.9	0.06	1.52	0.06	1.4
W28145Z	9	E2	1332	12.38	314.6	1.03	26.2	0.06	1.52	0.06	1.4
W28146Z	10	E2	1480	13.70	348.1	1.14	29.0	0.06	1.52	0.06	1.4
W28147Z	11	E2	1628	14.06	357.2	1.17	29.8	0.06	1.52	0.06	1.4
W28148Z	12	E2	1776	14.06	357.2	1.17	29.8	0.08	2.03	0.06	1.4

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 8 AWG, Unshielded - 10 AWG
Uninsulated Ground Wire, Thermoset Jacket

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm

8 AWG • Unshielded - 10 AWG Uninsulated Ground Wire • Thermoset Jacket • Type TC

Flexible Stranded (7 x 19 x 29) TC Conductors • XLPE Insulation • LSZH Jacket									
28149Z	2	E2	384	6.00	152.4	0.60	15.2	0.06	1.52
28150Z	3	E2	576	6.40	162.6	0.63	16.0	0.06	1.52
28151Z	4	E2	768	7.00	177.8	0.69	17.5	0.06	1.52

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

8 AWG • Unshielded - 10 AWG Uninsulated Ground Wire • Bronze Braid Armor • Thermoset Jacket • Type TC

Flexible Stranded (7 x 19 x 29) TC Conductors • XLPE Insulation • LSZH Jacket											
Z28149Z	2	E2	296	9.14	232.2	0.76	19.3	0.06	1.52	0.06	1.4
Z28150Z	3	E2	296	9.50	241.3	0.79	20.1	0.06	1.52	0.06	1.4
Z28151Z	4	E2	444	10.22	259.6	0.85	21.6	0.06	1.52	0.06	1.4

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

8 AWG • Unshielded - 10 AWG Uninsulated Ground Wire • Continuous Armor • Thermoset Jacket • Type MC

Flexible Stranded (7 x 19 x 29) TC Conductors • XLPE Insulation • LSZH Jacket											
NOTE: Continuous armor cables are not DNV rated											
W28149Z	2	E2	296	10.46	265.8	0.87	22.1	0.06	1.52	0.06	1.4
W28150Z	3	E2	296	10.82	274.9	0.90	22.9	0.06	1.52	0.06	1.4
W28151Z	4	E2	444	11.54	293.2	0.96	24.4	0.06	1.52	0.06	1.4

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 6 AWG, Unshielded - 8 AWG
Uninsulated Ground Wire, Thermoset Jacket

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm

6 AWG • Unshielded - 8 AWG Uninsulated Ground Wire • Thermoset Jacket • Type TC

Flexible Stranded (7 x 19 x 27) TC Conductors • XLPE Insulation • LSZH Jacket									
28152Z	2	E2	610	6.8	172.7	0.67	17.0	0.06	1.52
28153Z	3	E2	915	7.2	182.9	0.71	18.0	0.06	1.52
28154Z	4	E2	1220	7.9	200.7	0.78	19.8	0.06	1.52

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

6 AWG • Unshielded - 8 AWG Uninsulated Ground Wire • Bronze Braid Armor • Thermoset Jacket • Type TC

Flexible Stranded (7 x 19 x 27) TC Conductors • XLPE Insulation • LSZH Jacket											
Z28152Z	2	E2	296	9.98	253.5	0.83	21.1	0.06	1.52	0.06	1.4
Z28153Z	2	E2	296	10.46	265.7	0.87	22.1	0.06	1.52	0.06	1.4
Z28154Z	3	E2	444	11.30	287.0	0.94	23.9	0.06	1.52	0.06	1.4

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

6 AWG • Unshielded - 8 AWG Uninsulated Ground Wire • Continuous Armor • Thermoset Jacket • Type MC

Flexible Stranded (7 x 19 x 27) TC Conductors • XLPE Insulation • LSZH Jacket											
NOTE: Continuous armor cables are not DNV rated											
W28152Z	2	E2	296	11.30	287.1	0.94	23.9	0.06	1.52	0.06	1.4
W28153Z	2	E2	296	11.78	299.3	0.98	24.9	0.06	1.52	0.06	1.4
W28154Z	3	E2	444	12.62	320.6	1.05	26.7	0.06	1.52	0.06	1.4

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 4 AWG, Unshielded - 8 AWG
Uninsulated Ground Wire, Thermoset Jacket

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm

4 AWG • Unshielded - 8 AWG Uninsulated Ground Wire • Thermoset Jacket • Type TC

Flexible Stranded (7 x 19 x 25) TC Conductors • XLPE Insulation • LSZH Jacket									
28155Z	2	E2	970	7.7	195.6	0.77	19.6	0.06	1.52
28156Z	3	E2	1455	8.2	208.3	0.81	20.6	0.08	2.03
28157Z	4	E2	1940	9.5	241.3	0.94	23.9	0.08	2.03

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

4 AWG • Unshielded - 8 AWG Uninsulated Ground Wire • Bronze Braid Armor • Thermoset Jacket • Type TC

Flexible Stranded (7 x 19 x 25) TC Conductors • XLPE Insulation • LSZH Jacket											
Z28155Z	2	E2	970	11.18	284.0	0.93	23.7	0.06	1.52	0.06	1.4
Z28156Z	2	E2	1455	11.66	296.2	0.97	24.7	0.08	2.03	0.06	1.4
Z28157Z	3	E2	1940	13.22	335.8	1.10	28.0	0.08	2.03	0.06	1.4

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

4 AWG • Unshielded - 8 AWG Uninsulated Ground Wire • Continuous Armor • Thermoset Jacket • Type MC

Flexible Stranded (7 x 19 x 25) TC Conductors • XLPE Insulation • LSZH Jacket											
NOTE: Continuous armor cables are not DNV rated											
W28155Z	2	E2	970	12.50	317.6	1.04	26.5	0.06	1.52	0.06	1.4
W28156Z	2	E2	1455	12.98	329.8	1.08	27.5	0.08	2.03	0.06	1.4
W28157Z	3	E2	1940	14.54	369.4	1.21	30.8	0.08	2.03	0.06	1.4

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 2 AWG, Unshielded - 6 AWG
Uninsulated Ground Wire, Thermoset Jacket

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm

2 AWG • Unshielded - 6 AWG Uninsulated Ground Wire • Thermoset Jacket • Type TC

Flexible Stranded (7 x 19 x 23) TC Conductors • XLPE Insulation • LSZH Jacket									
28158Z	2	E2	1544	9.3	236.2	0.93	23.6	0.08	2.03
28159Z	3	E2	2316	9.8	248.9	0.98	24.9	0.08	2.03
28160Z	4	E2	3088	10.9	276.9	1.09	27.7	0.08	2.03

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

2 AWG • Unshielded - 6 AWG Uninsulated Ground Wire • Bronze Braid Armor • Thermoset Jacket • Type TC

Flexible Stranded (7 x 19 x 23) TC Conductors • XLPE Insulation • LSZH Jacket											
Z28158Z	2	E2	1544	13.10	332.7	1.09	27.7	0.08	2.03	0.06	1.4
Z28159Z	2	E2	2316	13.70	348.0	1.14	29.0	0.08	2.03	0.06	1.4
Z28160Z	3	E2	3088	15.02	381.5	1.25	31.8	0.08	2.03	0.06	1.4

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

2 AWG • Unshielded - 6 AWG Uninsulated Ground Wire • Continuous Armor • Thermoset Jacket • Type MC

Flexible Stranded (7 x 19 x 23) TC Conductors • XLPE Insulation • LSZH Jacket											
NOTE: Continuous armor cables are not DNV rated											
W28158Z	2	E2	1544	14.42	366.4	1.20	30.5	0.08	2.03	0.06	1.4
W28159Z	2	E2	2316	15.02	381.6	1.25	31.8	0.08	2.03	0.06	1.4
W28160Z	3	E2	3088	16.46	418.2	1.37	34.8	0.08	2.03	0.06	1.5

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 1 AWG to 4/0 AWG, Unshielded, Thermoset Jacket

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm
1 AWG • Unshielded - 6AWG Uninsulated Ground Wire • Thermoset Jacket • Type TC											
Flexible Stranded (7 x 19 x 22) TC Conductors • XLPE Insulation • LSZH Jacket											
28161Z	2	E2	2919	12.00	304.8	1.19	30.2	0.08	2.0	—	—
1 AWG • Unshielded - 6AWG Uninsulated Ground Wire • Bronze Braid Armor • Thermoset Jacket • Type TC											
Flexible Stranded (7 x 19 x 22) TC Conductors • XLPE Insulation • LSZH Jacket											
Z28161Z	2	E2	2919	16.55	420.3	1.38	35.0	0.08	2.0	0.06	1.52
1 AWG • Unshielded - 6AWG Uninsulated Ground Wire • Continuous Armor • Thermoset Jacket • Type MC											
Flexible Stranded (7 x 19 x 22) TC Conductors • XLPE Insulation • LSZH Jacket NOTE: Continuous armor cables are not DNV rated											
W28161Z	2	E2	2919	17.66	448.7	1.47	37.4	0.08	2.0	0.06	1.52
1/0 AWG • Unshielded - 6AWG Uninsulated Ground Wire • Thermoset Jacket • Type TC											
Flexible Stranded (7 x 19 x 21) TC Conductors • XLPE Insulation • LSZH Jacket											
28167Z	2	E2	1690	11.40	289.6	1.13	28.7	0.08	2.0	—	—
28168Z	3	E2	2535	12.10	307.3	1.21	30.7	0.08	2.1	—	—
28169Z	4	E2	3380	13.20	335.3	1.32	33.5	0.08	2.1	—	—
1/0 AWG • Unshielded - 6AWG Uninsulated Ground Wire • Bronze Braid Armor • Thermoset Jacket • Type TC											
Flexible Stranded (7 x 19 x 21) TC Conductors • XLPE Insulation • LSZH Jacket											
Z28167Z	2	E2	1690	15.50	393.7	1.29	32.8	0.08	2.0	0.06	1.4
Z28168Z	3	E2	2535	16.79	426.4	1.40	35.5	0.08	2.1	0.06	1.5
Z28169Z	4	E2	3380	18.11	459.9	1.51	38.3	0.08	2.1	0.06	1.5
1/0 AWG • Unshielded - 6AWG Uninsulated Ground Wire • Continuous Armor • Thermoset Jacket • Type MC											
Flexible Stranded (7 x 19 x 21) TC Conductors • XLPE Insulation • LSZH Jacket NOTE: Continuous armor cables are not DNV rated											
W28167Z	2	E2	1690	16.94	430.4	1.41	35.9	0.08	2.0	0.06	1.5
W28168Z	3	E2	2535	17.90	454.8	1.49	37.9	0.08	2.1	0.06	1.5
W28169Z	4	E2	3380	19.34	491.3	1.61	40.9	0.08	2.1	0.07	1.7
2/0 AWG • Unshielded - 6AWG Uninsulated Ground Wire • Thermoset Jacket • Type TC											
Flexible Stranded (7 x 19 x 20) TC Conductors • XLPE Insulation • LSZH Jacket											
28170Z	2	E2	2130	12.20	309.9	1.21	30.7	0.08	2.1	—	—
28171Z	3	E2	3195	13.00	330.2	1.30	33.0	0.08	2.1	—	—
28172Z	4	E2	4260	14.30	363.2	1.43	36.3	0.08	2.1	—	—
2/0 AWG • Unshielded - 6AWG Uninsulated Ground Wire • Bronze Braid Armor • Thermoset Jacket • Type TC											
Flexible Stranded (7 x 19 x 20) TC Conductors • XLPE Insulation • LSZH Jacket											
Z28170Z	2	E2	2130	16.79	426.4	1.40	35.5	0.08	2.1	0.06	1.5
Z28171Z	3	E2	3195	17.87	453.8	1.49	37.8	0.08	2.1	0.06	1.5
Z28172Z	4	E2	4260	19.43	493.4	1.62	41.1	0.08	2.1	0.06	1.5
2/0 AWG • Unshielded - 6AWG Uninsulated Ground Wire • Continuous Armor • Thermoset Jacket • Type MC											
Flexible Stranded (7 x 19 x 20) TC Conductors • XLPE Insulation • LSZH Jacket NOTE: Continuous armor cables are not DNV rated											
W28170Z	2	E2	2130	17.90	454.8	1.49	37.9	0.08	2.1	0.06	1.5
W28171Z	3	E2	3195	18.98	482.2	1.58	40.2	0.08	2.1	0.06	1.5
W28172Z	4	E2	4260	20.66	524.9	1.72	43.7	0.08	2.1	0.07	1.7

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Control Cable

600 V Type TC (or MC) Cables, 1 AWG to 4/0 AWG, Unshielded, Thermoset Jacket

Part No.	Conductors	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

3/0 AWG • Unshielded - 6AWG Uninsulated Ground Wire • Thermoset Jacket • Type TC

Flexible Stranded (7 x 19 x 19) TC Conductors • XLPE Insulation • LSZH Jacket											
28173Z	2	E2	2686	14.20	360.7	1.41	35.8	0.08	2.1	—	—
28174Z	3	E2	4029	15.20	386.1	1.51	38.4	0.08	2.1	—	—
28175Z	4	E2	5372	15.50	393.7	1.55	39.4	0.08	2.1	—	—

3/0 AWG • Unshielded - 6AWG Uninsulated Ground Wire • Bronze Braid Armor • Thermoset Jacket • Type TC

Flexible Stranded (7 x 19 x 19) TC Conductors • XLPE Insulation • LSZH Jacket											
Z28173Z	2	E2	2686	19.19	487.3	1.60	40.6	0.08	2.1	0.06	1.5
Z28174Z	3	E2	4029	20.51	520.9	1.71	43.4	0.08	2.1	0.07	1.7
Z28175Z	4	E2	5372	20.99	533.1	1.75	44.4	0.08	2.1	0.07	1.7

3/0 AWG • Unshielded - 6AWG Uninsulated Ground Wire • Continuous Armor • Thermoset Jacket • Type MC

Flexible Stranded (7 x 19 x 19) TC Conductors • XLPE Insulation • LSZH Jacket											
NOTE: Continuous armor cables are not DNV rated											
W28173Z	2	E2	2686	20.42	518.8	1.70	43.2	0.08	2.1	0.07	1.7
W28174Z	3	E2	4029	21.62	549.2	1.80	45.8	0.08	2.1	0.07	1.7
W28175Z	4	E2	5372	22.10	561.4	1.84	46.8	0.08	2.1	0.07	1.7

4/0 AWG • Unshielded - 6AWG Uninsulated Ground Wire • Thermoset Jacket • Type TC

Flexible Stranded (7 x 19 x 18) TC Conductors • XLPE Insulation • LSZH Jacket											
28176Z	2	E2	3386	13.20	335.3	1.31	33.3	0.08	2.1	—	—
28177Z	3	E2	5078	15.20	386.1	1.51	38.4	0.08	2.1	—	—
28178Z	4	E2	6771	17.50	444.5	1.75	44.5	0.12	3.0	—	—

4/0 AWG • Unshielded - 6AWG Uninsulated Ground Wire • Bronze Braid Armor • Thermoset Jacket • Type TC

Flexible Stranded (7 x 19 x 18) TC Conductors • XLPE Insulation • LSZH Jacket											
Z28176Z	2	E2	3386	17.99	456.9	1.50	38.1	0.08	2.1	0.06	1.5
Z28177Z	3	E2	5078	20.51	520.9	1.71	43.4	0.08	2.1	0.07	1.7
Z28178Z	4	E2	6771	23.39	594.0	1.95	49.5	0.12	3.0	0.07	1.7

4/0 AWG • Unshielded - 6AWG Uninsulated Ground Wire • Continuous Armor • Thermoset Jacket • Type MC

Flexible Stranded (7 x 19 x 18) TC Conductors • XLPE Insulation • LSZH Jacket											
NOTE: Continuous armor cables are not DNV rated											
W28176Z	2	E2	3386	19.10	485.2	1.59	40.4	0.08	2.1	0.06	1.5
W28177Z	3	E2	5078	21.62	549.2	1.80	45.8	0.08	2.1	0.07	1.7
W28178Z	4	E2	6771	24.50	622.4	2.04	51.9	0.12	3.0	0.07	1.7

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Instrumentation Cable

600 V Type TC (or MC) Cables



Featured Options:

- Bronze Braid Armoring
- Continuous Aluminum Armor (ABS) - Type MC
- LSZH Thermoset Jacket (Standard)
- Type P Rated Jacket
- Sunlight and Oil Resistant
- Unshielded, overall shield, or individually shielded

Construction:


1. **LSZH Thermoset Jacket**
2. **Beldfoil Shield**
3. **Flexible Stranded Tinned Copper Conductors**
4. **XLP Insulation**

NOTE: Also available on all options, bronze braid armor with LSZH second jacket, continuous armor with LSZH second jacket, overall foil shield 100% coverage (not pictured).

Certifications/Compliance

- ABS (American Bureau of Shipping)
- DNV (Det Norske Veritas)* pending
- IEEE 45 Electrical Installation on Shipboard
- IEEE 1580 Type P jacketing (recommended practice for marine cables for use on shipboard in fixed or floating facilities)
- UL 1309 marine shipboard cables
- IEC 60811-2-1 compliant for hydrocarbon resistance
- IEC 60754-1 compliant jacket for halogen content
- IEC 60754-2 compliant for acid gas emissions
- IEC 60092-350 electrical installation on ships
- UL 1277 TC-ER crush and impact resistance (UL TC for 2-conductor cables)
- IEEE 1202 and FT4 flame-resistance
- IEC 60332-3-22

*excludes continuous armored constructions



MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Instrumentation Cable

600 V Type TC (or MC) Cables, 18 AWG, Shielded, Thermoset Jacket

Part No.	Pairs	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm

18 AWG • Individually Shielded Pairs + Overall Shield 100% Beldfoil • Thermoset Jacket • Type TC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket									
1120Z	1	E2	59	3.20	81.3	0.32	8.1	0.05	1.2
3088Z	1	E1	67	3.20	81.3	0.32	8.1	0.05	1.2
1048Z	2	E1	140	5.10	129.5	0.51	13.0	0.05	1.2
1049Z	4	E1	258	6.30	160.0	0.63	16.0	0.05	1.3
1050Z	8	E1	350	8.00	203.2	0.79	20.1	0.06	1.6
1051Z	12	E1	728	10.10	256.5	1.01	25.7	0.06	1.6
1052Z	16	E1	963	11.30	287.0	1.12	28.4	0.08	2.1
1053Z	24	E1	1434	13.90	353.1	1.38	35.1	0.08	2.1
1054Z	36	E1	2139	15.90	403.9	1.58	40.1	0.08	2.1
1038Z	50	E1	2962	19.40	492.8	1.94	49.3	0.08	2.1

Part No.	Pairs	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

18 AWG • Individually Shielded Pairs + Overall Shield 100% Beldfoil • Bronze Braid Armor • Thermoset Jacket • Type TC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket											
Z1120Z	1	E2	59	5.57	141.6	0.46	11.8	0.05	1.2	0.06	1.4
Z3088Z	1	E1	67	5.57	141.6	0.46	11.8	0.05	1.2	0.06	1.4
Z1048Z	2	E1	140	7.85	199.5	0.65	16.6	0.05	1.2	0.06	1.4
Z1049Z	4	E1	258	9.29	236.1	0.77	19.7	0.05	1.3	0.06	1.4
Z1050Z	8	E1	350	11.21	284.8	0.93	23.7	0.06	1.6	0.06	1.4
Z1051Z	12	E1	728	13.85	351.9	1.15	29.3	0.06	1.6	0.06	1.4
Z1052Z	16	E1	963	15.17	385.4	1.26	32.1	0.08	2.1	0.06	1.4
Z1053Z	24	E1	1434	18.41	467.7	1.53	39.0	0.08	2.1	0.06	1.5
Z1054Z	36	E1	2139	20.93	531.7	1.74	44.3	0.08	2.1	0.07	1.7
Z1038Z	50	E1	2962	25.25	641.4	2.10	53.5	0.08	2.1	0.07	1.7

Part No.	Pairs	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

18 AWG • Individually Shielded Pairs + Overall Shield 100% Beldfoil • Continuous Armor • Thermoset Jacket • Type MC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket											
NOTE: Continuous armor cables are not DNV rated											
W1120Z	1	E2	59	7.10	180.4	0.59	15.0	0.05	1.2	0.06	1.4
W3088Z	1	E1	67	7.10	180.4	0.59	15.0	0.05	1.2	0.06	1.4
W1048Z	2	E1	140	9.38	238.4	0.78	19.9	0.05	1.2	0.06	1.4
W1049Z	4	E1	258	10.82	274.9	0.90	22.9	0.05	1.3	0.06	1.4
W1050Z	8	E1	350	12.74	323.7	1.06	27.0	0.06	1.6	0.06	1.4
W1051Z	12	E1	728	15.38	390.8	1.28	32.6	0.06	1.6	0.06	1.4
W1052Z	16	E1	963	16.82	427.3	1.40	35.6	0.08	2.1	0.06	1.5
W1053Z	24	E1	1434	20.06	509.6	1.67	42.5	0.08	2.1	0.07	1.7
W1054Z	36	E1	2139	22.46	570.6	1.87	47.5	0.08	2.1	0.07	1.7
W1038Z	50	E1	2962	26.78	680.3	2.23	56.7	0.08	2.1	0.07	1.7

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Instrumentation Cable

600 V Type TC (or MC) Cables, 18 AWG, Shielded, Thermoset Jacket



Part No.	Triads	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm

18 AWG • Individually Shielded Triads + Overall Shield 100% Beldfoil • Thermoset Jacket • Type TC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket									
1121Z	1	E2	81	3.30	83.8	0.32	8.1	0.05	1.2
3089Z	1	E1	90	3.30	83.8	0.32	8.1	0.05	1.2
3064Z	2	E1	185	6.00	152.4	0.59	15.0	0.05	1.2
1093Z	4	E1	347	6.90	175.3	0.68	17.3	0.06	1.6
1094Z	8	E1	672	9.40	238.8	0.94	23.9	0.06	1.6
1095Z	12	E1	997	11.30	287.0	1.13	28.7	0.08	2.1
1096Z	24	E1	1971	15.60	396.2	1.56	39.6	0.08	2.1

Part No.	Triads	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

18 AWG • Individually Shielded Triads + Overall Shield 100% Beldfoil • Bronze Braid Armor • Thermoset Jacket • Type TC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket											
Z1121Z	1	E2	81	5.57	141.6	0.46	11.8	0.05	1.2	0.055	1.4
Z3089Z	1	E1	90	5.57	141.6	0.46	11.8	0.05	1.2	0.055	1.4
Z3064Z	2	E1	185	8.81	223.9	0.73	18.7	0.05	1.2	0.055	1.4
Z1093Z	4	E1	347	9.89	251.3	0.82	20.9	0.06	1.6	0.055	1.4
Z1094Z	8	E1	672	13.01	330.5	1.08	27.5	0.06	1.6	0.055	1.4
Z1095Z	12	E1	997	15.29	388.5	1.27	32.4	0.08	2.1	0.055	1.4
Z1096Z	24	E1	1971	20.69	525.6	1.72	43.8	0.08	2.1	0.065	1.7

Part No.	Triads	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

18 AWG • Individually Shielded Triads + Overall Shield 100% Beldfoil • Continuous Armor • Thermoset Jacket • Type MC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket											
NOTE: Continuous armor cables are not DNV rated											
W1121Z	1	E2	81	7.10	180.4	0.59	15.0	0.05	1.2	0.06	1.4
W3089Z	1	E1	90	7.10	180.4	0.59	15.0	0.05	1.2	0.06	1.4
W3064Z	2	E1	185	10.34	262.7	0.86	21.9	0.05	1.2	0.06	1.4
W1093Z	4	E1	347	11.42	290.2	0.95	24.2	0.06	1.6	0.06	1.4
W1094Z	8	E1	672	14.54	369.4	1.21	30.8	0.06	1.6	0.06	1.4
W1095Z	12	E1	997	16.94	430.4	1.41	35.9	0.08	2.1	0.06	1.5
W1096Z	24	E1	1971	22.22	564.5	1.85	47.0	0.08	2.1	0.07	1.7

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Instrumentation Cable

600 V Type TC (or MC) Cables, 16 AWG, Shielded,
Thermoset Jacket

Part No.	Pairs	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm

16 AWG • Individually Shielded Pairs + Overall Shield 100% Beldfoil • Thermoset Jacket • Type TC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket									
1118Z	1	E2	105	3.50	88.9	0.34	8.64	0.05	1.2
3090Z	1	E1	105	3.50	88.9	0.34	8.64	0.05	1.2
1055Z	2	E1	223	5.90	149.9	0.58	14.73	0.05	1.2
1037Z	3	E1	290	6.20	157.5	0.62	15.75	0.05	1.2
1039Z	4	E1	411	6.80	172.7	0.68	17.27	0.06	1.6
1040Z	6	E1	428	8.00	203.2	0.80	20.32	0.06	1.6
1041Z	8	E1	786	9.00	228.6	0.90	22.86	0.06	1.6
1042Z	12	E1	1161	11.00	279.4	1.10	27.94	0.09	2.2
1043Z	16	E1	1537	12.30	312.4	1.22	30.99	0.09	2.2
1044Z	20	E1	1912	13.60	345.4	1.36	34.54	0.09	2.2
1045Z	24	E1	2287	15.20	386.1	1.51	38.35	0.09	2.2
1046Z	36	E1	3413	18.10	459.7	1.80	45.72	0.09	2.2
1047Z	50	E1	4726	21.20	538.5	2.12	53.85	0.12	3.0

Part No.	Pairs	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

16 AWG • Individually Shielded Pairs + Overall Shield 100% Beldfoil • Bronze Braid Armor • Thermoset Jacket • Type TC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket											
Z1118Z	1	E2	105	5.81	147.7	0.48	12.3	0.05	1.2	0.06	1.4
Z3090Z	1	E1	105	5.81	147.7	0.48	12.3	0.05	1.2	0.06	1.4
Z1055Z	2	E1	223	8.69	220.8	0.72	18.4	0.05	1.2	0.06	1.4
Z1037Z	3	E1	290	9.17	233.0	0.76	19.4	0.05	1.2	0.06	1.4
Z1039Z	4	E1	411	9.89	251.3	0.82	20.9	0.06	1.6	0.06	1.4
Z1040Z	6	E1	428	11.33	287.9	0.94	24.0	0.06	1.6	0.06	1.4
Z1041Z	8	E1	786	12.53	318.3	1.04	26.5	0.06	1.6	0.06	1.4
Z1042Z	12	E1	1161	14.93	379.3	1.24	31.6	0.09	2.2	0.06	1.4
Z1043Z	16	E1	1537	16.49	418.9	1.37	34.9	0.09	2.2	0.06	1.5
Z1044Z	20	E1	1912	18.17	461.6	1.51	38.5	0.09	2.2	0.06	1.5
Z1045Z	24	E1	2287	20.09	510.4	1.67	42.5	0.09	2.2	0.07	1.7
Z1046Z	36	E1	3413	23.57	598.8	1.96	49.9	0.09	2.2	0.07	1.7
Z1047Z	50	E1	4726	27.41	696.3	2.28	58.0	0.12	3.0	0.07	1.7

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Instrumentation Cable

600 V Type TC (or MC) Cables, 16 AWG, Shielded, Thermoset Jacket

Part No.	Pairs	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

16 AWG • Individually Shielded Pairs + Overall Shield 100% Beldfoil • Continuous Armor • Thermoset Jacket • Type MC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket <small>NOTE: Continuous armor cables are not DNV rated</small>											
W1118Z	1	E2	105	7.34	186.5	0.61	15.5	0.05	1.2	0.06	1.4
W3090Z	1	E1	105	7.34	186.5	0.61	15.5	0.05	1.2	0.06	1.4
W1055Z	2	E1	223	10.22	259.7	0.85	21.6	0.05	1.2	0.06	1.4
W1037Z	3	E1	290	10.70	271.9	0.89	22.7	0.05	1.2	0.06	1.4
W1039Z	4	E1	411	11.42	290.2	0.95	24.2	0.06	1.6	0.06	1.4
W1040Z	6	E1	428	12.86	326.7	1.07	27.2	0.06	1.6	0.06	1.4
W1041Z	8	E1	786	14.06	357.2	1.17	29.8	0.06	1.6	0.06	1.4
W1042Z	12	E1	1161	16.58	421.2	1.38	35.1	0.09	2.2	0.06	1.5
W1043Z	16	E1	1537	18.02	457.8	1.50	38.2	0.09	2.2	0.06	1.5
W1044Z	20	E1	1912	19.82	503.5	1.65	42.0	0.09	2.2	0.07	1.7
W1045Z	24	E1	2287	21.62	549.2	1.80	45.8	0.09	2.2	0.07	1.7
W1046Z	36	E1	3413	25.10	637.6	2.09	53.1	0.09	2.2	0.07	1.7
W1047Z	50	E1	4726	29.30	744.3	2.44	62.0	0.12	3.0	0.08	2.0

Part No.	Triads	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm

16 AWG • Individually Shielded Triads + Overall Shield 100% Beldfoil • Thermoset Jacket • Type TC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket									
1119Z	1	E2	129	3.60	91.4	0.35	8.9	0.05	1.2
3091Z	1	E1	129	3.60	91.4	0.35	8.9	0.05	1.2
1097Z	4	E1	554	7.40	188.0	0.74	18.8	0.06	1.6
1098Z	8	E1	1072	10.20	259.1	1.02	25.9	0.09	2.2
1099Z	12	E1	1590	12.40	315.0	1.24	31.5	0.09	2.2
3118Z	16	E1	1771	15.10	383.5	1.51	38.4	0.09	2.2
1100Z	24	E1	3144	17.90	454.7	1.78	45.2	0.09	2.2
3130Z	36	E1	3600	22.60	574.0	2.26	57.4	0.11	2.8

Part No.	Triads	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

16 AWG • Individually Shielded Triads + Overall Shield 100% Beldfoil • Bronze Braid Armor • Thermoset Jacket • Type TC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket											
Z1119Z	1	E2	129	9.77	248.0	0.38	9.8	0.05	1.2	0.06	1.4
Z3091Z	1	E1	129	9.77	248.0	0.38	9.8	0.05	1.2	0.06	1.4
Z1097Z	4	E1	554	20.11	510.8	0.79	20.1	0.06	1.6	0.06	1.4
Z1098Z	8	E1	1072	27.22	691.4	1.07	27.2	0.09	2.2	0.06	1.4
Z1099Z	12	E1	1590	33.25	844.4	1.31	33.2	0.09	2.2	0.06	1.5
Z3118Z	16	E1	1771	40.10	1018.6	1.58	40.1	0.09	2.2	0.07	1.7
Z1100Z	24	E1	3144	46.96	1192.8	1.85	47.0	0.09	2.2	0.07	1.7
Z3130Z	36	E1	3600	59.15	1502.5	2.33	59.2	0.11	2.8	0.08	2.0

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff UL Instrumentation Cable

600 V Type TC (or MC) Cables, 16 AWG, Shielded,
Thermoset Jacket



Part No.	Triads	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

16 AWG • Individually Shielded Triads + Overall Shield 100% Beldfoil • Continuous Armor • Thermoset Jacket • Type MC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket NOTE: Continuous armor cables are not DNV rated											
W1119Z	1	E2	129	13.00	330.3	0.51	13.0	0.05	1.2	0.06	1.4
W3091Z	1	E1	129	13.00	330.3	0.51	13.0	0.05	1.2	0.06	1.4
W1097Z	4	E1	554	22.91	581.9	0.90	22.9	0.06	1.6	0.06	1.4
W1098Z	8	E1	1072	30.02	762.6	1.18	30.0	0.09	2.2	0.06	1.4
W1099Z	12	E1	1590	35.61	904.5	1.40	35.6	0.09	2.2	0.06	1.5
W3118Z	16	E1	1771	42.47	1078.7	1.67	42.5	0.09	2.2	0.07	1.7
W1100Z	24	E1	3144	49.33	1252.9	1.94	49.3	0.09	2.2	0.07	1.7
W3130Z	36	E1	3600	61.52	1562.6	2.42	61.5	0.11	2.8	0.08	2.0

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Instrumentation Cable

600 V Type TC (or MC) Cables, 14 AWG, Shielded, Thermoset Jacket

Part No.	Pairs	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

14 AWG • Overall Shield 100% Beldfoil • Thermoset Jacket • Type TC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket

3080Z	1	E1	160	3.70	94.0	0.37	9.4	0.05	1.2	—	—
-------	---	----	-----	------	------	------	-----	------	-----	---	---

14 AWG • Overall Shield 100% Beldfoil • Bronze Braid Armor • Thermoset Jacket • Type TC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket

Z3080Z	1	E1	160	6.17	0.6	0.51	13.1	0.05	1.2	0.06	1.4
--------	---	----	-----	------	-----	------	------	------	-----	------	-----

14 AWG • Individually Shielded Pairs + Overall Shield 100% Beldfoil • Continuous Armor • Thermoset Jacket • Type MC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket NOTE: Continuous armor cables are not DNV rated

W3080Z	1	E1	160	7.70	195.7	0.64	16.3	0.05	1.2	0.06	1.4
--------	---	----	-----	------	-------	------	------	------	-----	------	-----

Part No.	Triads	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

14 AWG • Overall Shield 100% Beldfoil Triads • Thermoset Jacket • Type TC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket

3081Z	1	E1	200	3.80	96.5	0.38	9.7	0.05	1.2	—	—
-------	---	----	-----	------	------	------	-----	------	-----	---	---

14 AWG • Overall Shield 100% Beldfoil Triads • Bronze Braid Armor • Thermoset Jacket • Type TC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket

Z3081Z	1	E1	200	6.29	159.9	0.52	13.3	0.05	1.2	0.055	1.4
--------	---	----	-----	------	-------	------	------	------	-----	-------	-----

14 AWG • Individually Shielded Triads + Overall Shield 100% Beldfoil • Continuous Armor • Thermoset Jacket • Type MC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket NOTE: Continuous armor cables are not DNV rated

W3081Z	1	E1	200	7.82	198.7	0.65	16.6	0.05	1.2	0.055	1.4
--------	---	----	-----	------	-------	------	------	------	-----	-------	-----

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff UL Instrumentation Cable

600 V Type TC (or MC) Cables, 12 AWG, Shielded,
Thermoset Jacket

Part No.	Pairs	Color Code	Pull Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
			Lbs	Inch	mm	Inch	mm	Inch	mm	Inch	mm

12 AWG • Overall Shield 100% Beldfoil • Thermoset Jacket • Type TC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket											
3103A	1	E1	253	4.10	104.1	0.41	10.4	0.05	1.2	—	—

12 AWG • Overall Shield 100% Beldfoil • Bronze Braid Armor • Thermoset Jacket • Type TC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket											
Z3103A	1	E1	253	6.86	174.2	0.57	14.5	0.05	1.2	0.06	1.4

14 AWG • Individually Shielded Pairs + Overall Shield 100% Beldfoil • Continuous Armor • Thermoset Jacket • Type MC

Flexible Stranded TC Conductors • XLPE Insulation • LSZH Jacket											
W3103A	1	E1	253	8.18	14.6	0.68	17.3	0.05	1.2	0.06	1.4

NOTE: Continuous armor cables are not DNV rated

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff

Variable Frequency Drive (VFD) Cables



It is important to select a motor drive cable that has been properly designed and engineered to address all the key technical issues that such a component faces.

In offshore environments with multiple drives, increased vulnerability to noise exists. This noise emission can sometimes be difficult to track down and eliminate and is likely the single most significant problem associated with VFD systems today. Unless a proper cable shielding design is present to control it, noise emission from a drive system cable can disrupt operations. Moreover, because a longer cable radiates more noise, the length of cable runs must be limited. That, in turn, puts a limitation on your shipboard layout. Choosing well-designed, robust VFD cables ensures motor uptime and reliability of the VFD system and also provides protection for any sensitive instrumentation and adjacent control systems.

- The MarineTuff VFD line features XLP conductors appropriate for 90°C wet/dry demands, Class I and II / Division 2 hazardous location ratings, and HaloarrestXLink™ low smoke zero halogen jackets (LSZH).
- All options are rated 600V UL 1277 TC-ER and 1000V UL Flexible Motor Supply, UL 1309, IEEE 1580 Type P, UL 1685 Vertical Tray Flame tested, RoHS compliant and CE approved.

Key Attributes

- Thermoset LSZH jacket standard
- Bronze braid armoring available as option
- ABS certified, DNV (pending)
- 10 year warranty

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff VFD Cable

Classic Foil/Braid Design Thermoset Low Smoke Zero Halogen




Features:

- Low Smoke Zero Halogen (LSZH) jacketed, Type P approved
- 300% ground for enhanced system reliability and human safety. Approximately 300% of 1 full-sized conductor in ground potential copper
- Finely stranded tinned copper conductors for ease of cable installation, high frequency performance, vibration, corrosion and heat resistance
- Low capacitance XLP insulation protects motor by reducing magnitude of reflected wave
- Foil/Braid shielding enables noise control, improves common mode current containment and prevents capacitive coupling

Certifications/Compliance:

- ABS (American Bureau of Shipping)
- DNV (Det Norske Veritas)* pending
- IEEE 45 Electrical Installation on Shipboard
- IEEE 1580 Type P Jacket IEEE recommended practice for use on shipboard in fixed or floating facilities
- UL 1309 marine shipboard cables
- IEC 60811-2-1 Hydrocarbon Resistant
- IEC 60754-1,-2 (acid gas emissions)
- 600V UL 1277 Type TC-ER
- 1000V UL Flexible Motor Supply
- IEEE 1202/383, CSA FT4 Flame Tests
- IEC 60332-3-22 Cat A Flame Test
- -40°C Cold Bend
- RHW-2/XHHW-2 Rated Conductors (16 AWG XHHW-2 only)
- 90°C Wet/Dry
- Oil Res II
- Sunlight Resistant



Construction:

1. 16 to 2 AWG - Three Finely-Stranded Tinned Copper (TC) Circuit Conductors with XLP Insulation
2. One Full-Sized Green/Yellow XLP Insulated Ground (Same AWG as Circuit Ground Conductors)
3. One Full-Sized, Tinned, Uninsulated Ground/Drain
4. Overall Duofoil® Shield + 85% TC Braid
5. LSZH Thermoset Jacket

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff VFD Cable

Classic Foil/Braid Design Thermoset Low Smoke Zero Halogen



Part No.	Conductor		Pulling Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
	AWG	Stranding	Lbs	Inch	mm	Inch	mm	Lbs	mm	Inch	mm

16 to 2 AWG • Thermoset Jacket

29500X	16	26x30	128	4.3	109.2	0.53	13.5	0.07	1.85	—	—
29501X	14	41x30	212	4.8	121.9	0.60	15.2	0.07	1.85	—	—
29502X	12	65x30	336	5.2	132	0.65	16.5	0.07	1.85	—	—
29503X	10	105x30	592	5.5	139.7	0.69	17.5	0.07	1.85	—	—
29504X	8	7x19x29	768	7.5	190.5	0.93	23.6	0.09	2.36	—	—
29505X	6	7x19x27	1220	8.0	203.2	1.02	25.9	0.09	2.36	—	—
29506X	4	7x19x25	1940	9.3	236.2	1.16	29.5	0.09	2.36	—	—
29507X	2	7x19x23	3088	10.8	273.1	1.31	33.3	0.09	2.36	—	—

Conductor Color Coding: ICEA Method 4: Black and Numbered, Green/Yellow Ground.

Part No.	Conductor		Pulling Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
	AWG	Stranding	Lbs	Inch	mm	Inch	mm	Lbs	mm	Inch	mm

16 to 2 AWG • Bronze Braid Armor • Thermoset Jacket

Z29500X	16	26x30	128	8.30	210.8	0.69	17.6	0.07	1.85	0.06	1.4
Z29501X	14	41x30	212	9.14	232.2	0.76	19.3	0.07	1.85	0.06	1.4
Z29502X	12	65x30	336	9.74	247.4	0.81	20.6	0.07	1.85	0.06	1.4
Z29503X	10	105x30	592	10.22	259.6	0.85	21.6	0.07	1.85	0.06	1.4
Z29504X	8	7x19x29	768	13.10	332.7	1.09	27.7	0.09	2.36	0.06	1.4
Z29505X	6	7x19x27	1220	14.18	360.2	1.18	30.0	0.09	2.36	0.06	1.4
Z29506X	4	7x19x25	1940	15.86	402.8	1.32	33.6	0.09	2.36	0.06	1.4
Z29507X	2	7x19x23	3088	17.78	451.6	1.48	37.6	0.09	2.36	0.06	1.5

Conductor Color Coding: ICEA Method 4: Black and Numbered, Green/Yellow Ground.

Part No.	Conductor		Pulling Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
	AWG	Stranding	Lbs	Inch	mm	Inch	mm	Lbs	mm	Inch	mm

16 to 2 AWG • Continuous Armor • Thermoset Jacket

W29500X	16	26x30	128	9.62	244.4	0.80	20.4	0.07	1.85	0.06	1.4
W29501X	14	41x30	212	10.46	265.8	0.87	22.1	0.07	1.85	0.06	1.4
W29502X	12	65x30	336	11.06	281.0	0.92	23.4	0.07	1.85	0.06	1.4
W29503X	10	105x30	592	11.54	293.2	0.96	24.4	0.07	1.85	0.06	1.4
W29504X	8	7x19x29	768	14.42	366.4	1.20	30.5	0.09	2.36	0.06	1.4
W29505X	6	7x19x27	1220	15.50	393.8	1.29	32.8	0.09	2.36	0.06	1.4
W29506X	4	7x19x25	1940	17.30	439.5	1.44	36.6	0.09	2.36	0.06	1.5
W29507X	2	7x19x23	3088	19.10	485.2	1.59	40.4	0.09	2.36	0.06	1.5

Conductor Color Coding: ICEA Method 4: Black and Numbered, Green/Yellow Ground. NOTE: Continuous armor cables are not DNV rated

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff VFD Cable


Classic Symmetrical Design Thermoset Low Smoke
Zero Halogen

Features:

- Low Smoke Zero Halogen (LSZH) jacketed, Type P approved
- 100% Ground - 3 Symmetrical Ground Conductors
- Finely stranded tinned copper conductors for ease of cable installation, high frequency performance, vibration, corrosion and heat resistance
- Low capacitance XLP insulation protects motor by reducing magnitude of reflected wave
- 100% Dual copper tape shielding for enhanced flexibility and noise control

Certifications/Compliance:

- ABS (American Bureau of Shipping)
- DNV (Det Norske Veritas)* pending
- IEEE 45 Electrical Installation on Shipboard
- IEEE 1580 Type P Jacket IEEE recommended practice for use on shipboard in fixed or floating facilities
- UL 1309 marine shipboard cables
- IEC 60811-2-1 Hydrocarbon Resistant
- IEC 60754-1,-2 (acid gas emissions)
- 600V UL 1277 Type TC-ER
- 1000V UL Flexible Motor Supply
- IEEE 1202/383, CSA FT4 Flame Tests
- IEC 60332-3-22 Cat A Flame Test
- -40°C Cold Bend
- XHHW-2 Rated Conductors
- 90°C Wet/Dry
- Oil Res II
- Sunlight Resistant



Construction:

1. 1 to 4/0 AWG - Three Finely-Stranded Tinned Copper (TC) Circuit Conductors with XLP Insulation
2. Three Symmetrical Bare Copper (BC) Uninsulated Grounds (equivalent to 1 full-sized ground)
3. Two Spiral Copper Tape Shields (100% Coverage)
4. LSZH Thermoset Jacket

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff VFD Cable

Classic Symmetrical Design Thermoset Low Smoke
Zero Halogen

Part No.	Conductor		Pulling Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
	AWG	Stranding	Lbs	Inch	mm	Inch	mm	Lbs	mm	Inch	mm

1 to 4/0 AWG • Thermoset Jacket

29528X	1	7X19X22	2650	12.00	304.8	1.20	30.5	0.08	2.1	—	—
29529X	1/0	7X19X21	3537	12.90	327.7	1.29	32.8	0.08	2.1	—	—
29530X	2/0	7X19X20	4200	14.00	355.6	1.40	35.6	0.08	2.1	—	—
29531X	3/0	7X19X19	5025	15.20	386.1	1.52	38.6	0.08	2.1	—	—
29532X	4/0	7X19X18	6670	16.80	426.7	1.68	42.7	0.08	2.1	—	—

Conductor Color Coding: ICEA Method 4: Black and Numbered, Green/Yellow Ground.

Part No.	Conductor		Pulling Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
	AWG	Stranding	Lbs	Inch	mm	Inch	mm	Lbs	mm	Inch	mm

1 to 4/0 AWG • Bronze Braid Armor • Thermoset Jacket

Z29528X	1	7X19X22	2650	16.67	423.3	1.39	35.3	0.08	2.1	0.06	1.5
Z29529X	1/0	7X19X21	3537	17.75	450.8	1.48	37.6	0.08	2.1	0.06	1.5
Z29530X	2/0	7X19X20	4200	19.07	484.3	1.59	40.4	0.08	2.1	0.06	1.5
Z29531X	3/0	7X19X19	5025	20.63	523.9	1.72	43.7	0.08	2.1	0.07	1.7
Z29532X	4/0	7X19X18	6670	22.55	572.7	1.88	47.7	0.08	2.1	0.07	1.7

Conductor Color Coding: ICEA Method 4: Black and Numbered, Green/Yellow Ground.

Part No.	Conductor		Pulling Tension (Max)	Bend Radius (Min)		OD (Nom)		Jacket Thickness		Outer Jacket Thickness	
	AWG	Stranding	Lbs	Inch	mm	Inch	mm	Lbs	mm	Inch	mm

1 to 4/0 AWG • Continuous Armor • Thermoset Jacket

W29528X	1	7X19X22	2650	17.78	956.1	1.48	37.6	0.08	2.1	0.06	1.5
W29529X	1/0	7X19X21	3537	18.86	1014.2	1.57	39.9	0.08	2.1	0.06	1.5
W29530X	2/0	7X19X20	4200	20.30	1091.6	1.69	43.0	0.08	2.1	0.07	1.7
W29531X	3/0	7X19X19	5025	21.74	1169.0	1.81	46.0	0.08	2.1	0.07	1.7
W29532X	4/0	7X19X18	6670	23.66	1272.3	1.97	50.1	0.08	2.1	0.07	1.7

Conductor Color Coding: ICEA Method 4: Black and Numbered, Green/Yellow Ground. NOTE: Continuous armor cables are not DNV rated

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff

Foundation Fieldbus Cables



FOUNDATION Fieldbus is the dominant industrial network in offshore environments. Belden Fieldbus cables are designed to withstand the destructive effects of temperature extremes, humidity/moisture, dust and oil. In harsh environments such as oil and gas extraction ultraviolet radiation from extensive exposure to the sun can shorten cable life. With the high cost of downtime in such remote locations, investing in cable with proven performance and reliability can significantly reduce the likelihood of system failure.

Key Attributes

- Type P ratings on all 600V jackets and options
- LSZH jackets on all cables and options
- Bronze braid option on all cables
- ABS certified, DNV (pending)
- 10 year warranty
- Compliant with Fieldbus Spec IEC 61158-2 (ISA/SP-50)
- Excellent electrical characteristics
- Versions in 18 and 16 AWG stranded tinned copper conductors
- Standard multi-pair cables available in 2 to 12 pairs. Higher pair counts available upon request
- PLTC/ITC-ER, PLTC, and TC-ER versions
- C(UL) CIC Type TC on 600V XLP insulated products
- Suitable for use in Class 1, Div. 2 applications
- RoHS compliant and CE approved

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff FOUNDATION Fieldbus Cable

300V and 600V, 18 AWG Paired Cable, Type A,
Thermoset/Thermoplastic with or without Bronze Armoring




Featured Options:

- Low Smoke Zero Halogen - Both Thermoplastic and Thermoset Options
- Bronze braid armoring
- Additional AWG sizes and pair counts available upon request
- Sun Res
- Oil Res II (Thermoset)

Certifications/Compliance

- Marine approvals: ABS listed, DNV (pending)
- IEEE 1580 Type P Jacket - 600V Constructions
- UL 1277 Type TC-ER - 600V Constructions
- PLTC/ITC-ER - 300V Constructions
- NEC: CMG - 300V Constructions
- CEC: CMG FT4 - 300V Constructions
- IEC 60332-3-24 (Cat C)
- FT4/IEEE 1202
- IEC 60332-3-22
- IEC 60754-1 (Jacket)
- IEC 60754-2 (Jacket)



Construction:

1. 18 or 16 AWG Stranded Tinned Copper Conductors
2. XLP Insulation - 600V
Polyolefin Insulation - 300V
3. 100% Overall Foil Shield Coverage
Plus Individually Shielded Pairs on Multi-Pair Constructions
4. LSZH Thermoset or Thermoplastic Jacket

NOTE: Also available on all options, bronze braid armor with LSZH second jacket not pictured



MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff FOUNDATION Fieldbus Cable

300V and 600V, 18 AWG Paired Cable, Type A,
Thermoset/Thermoplastic with or without Bronze Armoring

Part No.	AWG	Pairs	OD (Nom)		Additional Features/Ratings	
			Inch	mm		
300V, 18 AWG Foundation Fieldbus						
Stranded (7 x 26) TC Conductors • Polyolefin Insulation • LSZH Jacket • TC Drain Wire • Beldfoil® Shielding						
Thermoset Jacket						
3076Z	18	1	0.38	9.7	CMG, PLTC-ER, ITC-ER, Direct Burial	
Thermoplastic Jacket						
3076T	18	1	0.38	9.7		
300V, 18 AWG Foundation Fieldbus, Bronze Armored						
Stranded (7 x 26) TC Conductors • Polyolefin Insulation • LSZH Jacket • TC Drain Wire • Beldfoil® Shielding						
Thermoset Jacket						
973076Z	18	1	0.52	13.3	CMG, PLTC-ER, ITC-ER, Direct Burial	
Thermoplastic Jacket						
773076T	18	1	0.52	13.3		
600 V, 18 AWG Foundation Fieldbus						
Stranded (7 x 26) TC Conductors • XLP Insulation • LSZH Jacket • TC Drain Wire • Beldfoil® Shielding						
Thermoset Jacket						
2118Z	18	1	0.35	8.8	TC-ER, ITC-ER, Direct Burial	
2119Z	18	2	0.60	15.2		
2120Z	18	5	0.75	19.0		
2121Z	18	8	0.93	23.6		
2122Z	18	12	1.12	28.5		
Thermoplastic Jacket						
2118T	18	1	0.35	8.8		
2119T	18	2	0.60	15.2		
2120T	18	5	0.75	19.0		
2121T	18	8	0.93	23.6		
2122T	18	12	1.12	28.5		

Conductor Color Code: Blue, Orange, Numbered Pairs.

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff FOUNDATION Fieldbus Cable

600V, 18 AWG Paired Cable, Type A



Part No.	AWG	Pairs	OD (Nom)		Additional Features/Ratings
			Inch	mm	
600V, 18 AWG Foundation Fieldbus - Bronze Armored					
Stranded (7x26) TC Conductors • XLP Insulation • LSZH Jacket • TC Drain Wire • Individually shielded pairs and overall Beldfoil Shielding					
Thermoset Jacket					
972118Z	18	1	0.48	12.5	TC-ER, ITC-ER, Direct Burial
972119Z	18	2	0.75	19.3	
972120Z	18	5	0.90	23.1	
972121Z	18	8	1.09	27.7	
972122Z	18	12	1.28	32.6	
Thermoplastic Jacket					
772118T	18	1	0.49	12.5	TC-ER, ITC-ER, Direct Burial
772119T	18	2	0.76	19.3	
772120T	18	5	0.91	23.1	
772121T	18	8	1.09	27.7	
772122T	18	12	1.28	32.6	

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff FOUNDATION Fieldbus Cable

600V, 16 AWG Paired Cable, Type A



Part No.	AWG	Pairs	OD (Nom)		Additional Features/Ratings
			Inch	mm	

600V, 16 AWG Foundation Fieldbus

Stranded (7x24) TC Conductors • XLP Insulation • LSZH Jacket • TC Drain Wire • Individually shielded pairs and overall Beldfoil Shielding

Thermoset Jacket

2127Z	16	1	0.37	9.5	TC-ER, ITC-ER, Direct Burial
2128Z	16	2	0.65	16.4	
2129Z	16	5	0.81	20.6	
2130Z	16	8	1.01	25.6	
2131Z	16	12	1.22	31.0	

Thermoplastic Jacket

2127T	16	1	0.37	9.5	TC-ER, ITC-ER, Direct Burial
2128T	16	2	0.65	16.4	
2129T	16	5	0.81	20.6	
2130T	16	8	1.01	25.6	
2131T	16	12	1.22	31.0	

600V, 16 AWG Foundation Fieldbus - Bronze Armored

Stranded (7x24) TC Conductors - XLP Insulation - LSZH Jacket - TC Drain Wire - Individually shielded pairs and overall Beldfoil Shielding

Thermoset Jacket

972127Z	16	1	0.52	13.2	TC-ER, ITC-ER, Direct Burial
972128Z	16	2	0.81	20.5	
972129Z	16	5	0.97	24.7	
972130Z	16	8	1.17	29.7	
972131Z	16	12	1.41	35.8	

Thermoplastic Jacket

772127T	16	1	0.51	13.2	TC-ER, ITC-ER, Direct Burial
772128T	16	2	0.80	20.5	
772129T	16	5	0.97	24.7	
772130T	16	8	1.16	29.7	
772131T	16	12	1.41	35.8	

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff

PROFIBUS-DP Cables



PROFIBUS is one of the largest open industrial fieldbuses in the world. As with most fieldbus systems, PROFIBUS can reduce operating costs, increase productivity, decrease time to market for new products, and improve product quality. And unlike standard 4-20mA controls, PROFIBUS can support up to 32 devices per segment — up to a total of 126 devices, depending on total system current.

The MarineTuff Profibus offering includes a 150-ohm twinax (twisted pair) cable that matches the impedance of your offshore system, allowing for maximum signal transmission. The cable incorporates an overall Beldfoil® shield plus a 65% tinned copper braid for maximum shielding effectiveness. It also carries a UL NEC Type PLTC listing to achieve maximum installation versatility. The stranded option provides additional flexibility during installation and in use. With the additional ABS rating and armoring options, the MarineTuff Profibus line will meet all the demands of your Marine applications.

Key Attributes

- LSZH jackets on all cable options
- UL NEC Type PLTC
- Overall Beldfoil shield plus 65% tinned copper braid
- Optimized for maximum signal transmission
- 10 year warranty

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff PROFIBUS-DP Cable

22 AWG, PLTC, Thermoset/Thermoplastic with or without Bronze Armoring



Featured Options:

- Low Smoke Zero Halogen jacket – Both Thermoplastic and Thermoset Options
- Multiple armoring options
- Sun Res
- Oil Res II (Thermoset)


Certifications/Compliance

- Marine approvals: ABS listed, DNV (pending)
- NEC: PLTC CMG
- CEC: CMG FT4
- FT4/IEEE 1202
- IEC 60332-3-22
- IEC 60754-1 (Jacket)
- IEC 60754-2 (Jacket)

Construction:

1. 22 AWG Bare Copper Conductors
2. Flame Retardant Foam Polyethylene Insulation
3. Overall Beldfoil® Shield (100% coverage)
4. Tinned Copper Braid Shield (65% coverage)
5. LSZH Thermoset or Thermoplastic Jacket

NOTE: Also available on all options, bronze braid armor with LSZH second jacket not pictured



MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff PROFIBUS-DP Cable

22 AWG, PLTC, Thermoset/Thermoplastic with or without Bronze Armoring



Part No.	OD (Nom)		Additional Features/Ratings
	Inch	mm	
22 AWG, 300V Single Pair Databus ISA/SP-50 Profibus Cable			
Solid BC Conductors • FRFPE Insulation • Overall Beldfoil® Shielding, plus Overall Tinned Copper Braid (65% coverage) • LSZH Outer Jacket			
Thermoset Jacket			
3079Z	0.43	10.9	PLTC-LS, CMG-LS
Thermoplastic Jacket			
3079T	0.43	10.9	
22 AWG, 300V Single Pair DataBus ISA/SP-50 Profibus Cable - with Bronze Armoring			
Solid BC Conductors • FRFPE Insulation • Overall Beldfoil® Shielding, plus Overall Tinned Copper Braid (65% coverage) • LSZH Outer Jacket			
Thermoset Jacket			
973079Z	0.59	15.0	PLTC-LS, CMG-LS
Thermoplastic Jacket			
773079T	0.59	15.0	

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff

RS-485 Cables



As a part of Belden's comprehensive portfolio of Industrial Ethernet cables, the MarineTuff RS-485 provides reliable connections as a standard from the control room to metering and pumping/compressor stations. Traditionally, RS-485 transmission in plenum applications required conduit to protect the cable, but Belden offers RS-485 cables that are CMP listed, they offer flame and smoke protection performance, and they are able to run in a plenum without conduit - without sacrificing electrical performance.

With manufacturing in ISO certified manufacturing facilities, Belden's state-of-the-art processes ensure quality in each product. Product consistency is a mainstay of our products.

Key Attributes

- LSZH jackets on all cable options
- UL NEC Type PLTC/CMG
- High foam density polyethylene insulation (FHDPE)
- Overall Beldfoil shield plus 65% tinned copper braid
- 10 year warranty

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff RS-485 Cable

PLTC/CM, Thermoset/Thermoplastic with or without Bronze Armoring

Featured Options:

- Low Smoke Zero Halogen jacket – both Thermoplastic and Thermoset Options
- Sun Res
- Oil Res II (Thermoset)


Certifications/Compliance

- Marine approvals: ABS listed, DNV (pending)
- NEC: CMG, PLTC
- CEC/C(UL): CMG FT4
- FT4/IEEE 1202
- IEC 60332-3-22
- IEC 60754-1 (Jacket)
- IEC 60754-2 (Jacket)

Construction:

1. 22 AWG Stranded Tinned Copper (TC) Conductors
2. Datalene® Insulation
3. Overall Beldfoil® Shield (100% coverage)
4. Tinned Copper Braid Shield (65% coverage)
5. Stranded Tinned Copper Drain Wire
6. LSZH Thermoset or Thermoplastic Jacket

NOTE: Also available on all options, bronze braid armor with LSZH second jacket not pictured



MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff RS-485 Cable

PLTC/CM, Thermoset/Thermoplastic with or without Bronze Armoring

Part No.	Pairs	OD (Nom)		Additional Features/Ratings	
		Inch	mm		
RS-485					
22 AWG (7x30) Stranded TC Conductors • Datalene Insulation • TC Drain Wire - Overall Beldfoil Shielding plus an overall tinned copper braid (65% coverage) • LSZH Outer Jacket					
Thermoset Jacket					
3105Z	1	0.40	10.2	CMG-LS, PLTC-LS	
3107Z	2	0.44	11.2		
3108Z	3	0.47	11.9		
3109Z	4	0.49	12.4		
Thermoplastic Jacket					
3105T	1	0.45	11.4		
3107T	2	0.49	12.4		
3108T	3	0.52	13.2		
3109T	4	0.49	12.4		
RS-485 - Bronze Armored					
22 AWG (7x30) Stranded TC Conductors • Datalene Insulation • TC Drain Wire - Overall Beldfoil Shielding plus an overall tinned copper braid (65% coverage) • LSZH Outer Jacket					
Thermoset Jacket					
973105Z	1	0.56	14.3	CMG-LS, PLTC-LS	
973107Z	2	0.60	15.3		
973108Z	3	0.63	16.0		
973109Z	4	0.65	16.6		
Thermoplastic Jacket					
773105T	1	0.61	15.5		
773107T	2	0.65	16.6		
773108T	3	0.68	17.3		
773109T	4	0.70	17.8		

BC = Bare Copper • PVC = Polyvinyl Chloride

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff™

ControlNet™



To ensure that Belden's ControlBus™ cables meet the high-speed, time-critical requirements for the operation of ControlNet offshore systems, these low-loss RG-6/U Type coaxial cables incorporate a Duobond Quad Shield for maximum signal integrity and run length. All products are sweep tested across a wide frequency range, ensuring that return loss, impedance and other critical performance features, meet the requirements of the ControlNet physical layer specification. ControlBus cables can be supplied with a bronze braid, aluminum or steel interlocked armor. Belden manufactures variations of the cable for different applications, identification needs, and environments.

Key Attributes

- Excellent electrical characteristics
- RoHS compliant and CE approved
- ABS certified, DNV (pending)
- Low Smoke Zero Halogen (LSZH) jackets on all cables
- Bronze Braid Optional
- 10-Year Warranty

ControlNet is a ControlNet International, Ltd. Trademark

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff ControlNet™ Cable

18 AWG, Duobond®-Quad Shielded Coaxial, Type RG6/U,
Thermoset/Thermoplastic with or without Bronze Armoring



Featured Options:

- Low Smoke Zero Halogen Jacket - Both Thermoplastic and Thermoset Options
- Multiple armoring options
- Sun Res
- Oil Res II (Thermoset)


Certifications/Compliance

- Marine approvals: ABS listed, DNV (pending)
- NEC: CMG CL2
- CEC: CMG FT4
- FT4/IEEE 1202
- IEC 60332-3-22
- IEC 60754-1 (Jacket)
- IEC 60754-2 (Jacket)

Construction:

1. Type RG6/U 18 AWG Solid Copper Covered Steel Conductors or 20 AWG Finely Stranded BC Conductor (High Flex)
2. Polyolefin Insulation
3. Quad-Shield Coverage (Foil Braid/Foil Braid)
4. LSZH Thermoset or Thermoplastic Jacket

NOTE: Also available on all options, bronze braid armor with LSZH second jacket not pictured



MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff ControlNet™ Cable

18 AWG, Duobond®-Quad Shielded Coaxial, Type RG6/U, Thermoset/Thermoplastic with or without Bronze Armoring

Part No.	AWG	OD (Nom)		Additional Features/Ratings
		Inch	mm	
Solid - Quad Shielded Coaxial, Type RG6/U				
18 AWG Solid BC-Covered Steel Conductor • Polyolefin Insulation • Duobond QuadShield • LSZH Jacket				
Thermoset Jacket				
3092Z	18	0.30	7.6	CMG-LS, CL2
Thermoplastic Jacket				
3092T	18	0.30	7.6	
Solid - Quad Shielded Coaxial, Type RG6/U - Bronze Armored				
18 AWG Solid BC-Covered Steel Conductor • Polyolefin Insulation • Duobond QuadShield • LSZH Jacket				
Thermoset Jacket				
973092Z	18	0.44	11.3	CMG-LS, CL2
Thermoplastic Jacket				
773092T	18	0.44	11.3	
Stranded - Quad Shielded Coaxial, Type RG6/U				
18 AWG Stranded (105x40) BC Conductor • Polyolefin Insulation • Duobond QuadShield • LSZH Jacket				
Thermoset Jacket				
3092FZ	20	0.31	7.7	CMG-LS, CL2
Thermoplastic Jacket				
3092FT	20	0.31	7.7	
Stranded - Quad Shielded Coaxial, Type RG6/U - Bronze Armored				
18 AWG Stranded (105x40) BC Conductor • Polyolefin Insulation • Duobond QuadShield • LSZH Jacket				
Thermoset Jacket				
973092F	20	0.45	11.4	CMG-LS, CL2
Thermoplastic Jacket				
773092F	20	0.45	11.4	

*Duobond IV is a four-layer shield: (1) Duobond II Foil, (2) TC Braid (94%), (3) Duofoil® Foil, (4) TC Braid (90%).

BC = Bare Copper • PVC = Polyvinyl Chloride

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff

Blue Hose Cables



The needs of real-time, high-throughput applications can be routinely met by the control network and the use of Belden Blue Hose cable. These cables are a robust physical media for the transmission of PLC/DCS signals. Backed by years of research and development, each Belden Blue Hose cable is manufactured to exacting quality standards. Belden Blue Hose cables are designed to give you unprecedented installation flexibility for Data Highway, SY/Net and many other PLC-I/O networks.

Key Attributes

- LSZH jackets on all cables and options
- Bronze braid options on all cables and options
- ABS certified, DNV (pending)
- 10 year warranty

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff Blue Hose Cable

18 AWG, 600V Twinaxial Cable Thermoset/Thermoplastic Jackets with or without Bronze Braid Armoring

Featured Options:

- Low Smoke Zero Halogen jacket – standard on all products
- Sunlight and Oil resistance
- Direct Burial
- Bronze braid armoring
- Sun Res
- Oil Res II (Thermoset)


Certifications/Compliance

- Marine approvals: ABS listed, DNV (pending)
- NEC/UL: CMG, TC
- C(UL): CMG
- FT4/IEEE 1202
- IEC 60332-3-22
- IEC 60754-1 (Jacket)
- IEC 60754-2 (Jacket)

Construction:

1. LSZH Thermoset Jacket
2. 100% Foil Shield Coverage
3. 55% tinned copper braid
4. Drain wire

NOTE: Also available on all options, bronze braid armor with LSZH second jacket not pictured



MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff Blue Hose Cable

18 AWG, 600V Twinaxial Cable Thermoset/Thermoplastic Jackets with or without Bronze Braid Armoring

Part No.	OD (Nom)		Additional Features/Ratings
	Inch	mm	
18 AWG, 600V Twinaxial Cable			
Stranded TC Conductors (7x26) • Polyolefin Insulation • Overall Beldfoil Shielding • LSZH Outer Jacket			
Thermoset Jacket			TC-LS, CMG-LS, ITC-LS
3072Z	0.42	10.6	
Thermoplastic Jacket			
3072T	0.42	10.6	
18 AWG, 600V Twinaxial Cable - with Bronze Braid Armor			
Stranded TC Conductors (7x26) • Polyolefin Insulation • Overall Beldfoil Shielding • LSZH Outer Jacket			
Thermoset Jacket			TC-LS, CMG-LS, ITC-LS
973072Z	0.57	14.7	
Thermoplastic Jacket			
773072T	0.57	14.7	

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff™

DeviceNet™



Widely used for maritime electronics, the MarineTuff Devicenet cables rugged design will support your offshore DeviceNet ODVA requirements. These cables provide device designers with the ability to implement desired network behavior of several communication objects into a device while the durable design allows these networks to run in the harshest environments. Whether connecting sensors or switching devices, the MarineTuff DeviceNet cables will offer the reliability you demand.

Key Attributes

- 600V Class 1 ODVA
- LSZH jackets on all cable options
- UL NEC TC-ER
- Overall Beldfoil shield plus 65% tinned copper braid
- XLPE insulation on the power pairs and F-R Polypropylene on the data pairs
- Able to occupy the same tray/conduit as 600V cables
- 10 year warranty

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff DeviceNet™ Cable

16 AWG, 600V Thermopet/Thermoplastic Jackets with
or without Bronze Braid Armoring



Featured Options:

- Low Smoke Zero Halogen jacket – standard on all products
- Multiple armoring options
- Sun Res
- Oil Res II (Thermoset)


Certifications/Compliance

- Marine approvals: ABS listed, DNV (pending)
- C(UL) AWM I/II A/B (Thermoset Only)
- NEC: TC-ER
- CEC: FT4
- FT4/IEEE 1202
- IEC 60332-3-22
- IEC 60754-1 (Jacket)
- IEC 60754-2 (Jacket)

Construction:

1. LSZH Thermoset Jacket
2. 100% Foil Shield Coverage
3. TC Braid Shield (65% coverage)
4. 18 AWG Data
5. 16 AWG Power

NOTE: Also available on all options, bronze braid armor with LSZH second jacket not pictured



MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff DeviceNet™ Cable

16 AWG, 600V Thermopset/Thermoplastic Jackets with or without Bronze Braid Armoring



Part No.	Pairs	OD (Nom)		Additional Features/Ratings
		Inch	mm	
16 AWG, 600V DeviceBus for ODVA DeviceNet				
Stranded TC Conductors (19x29) • XLPE Insulation (Thermoset) • PE Insulation (Thermoplastic) • Overall Beldfoil Shielding plus Overall Tinned Copper Braid (65% coverage) • LSZH Outer Jacket				
Thermoset Jacket		TC-LS, TC-ER, AWM I/II A/B		
7896Z	2	0.64	16.2	
Thermoplastic Jacket		TC-LS, TC-ER		
7896T	2	0.64	16.2	
16 AWG, 600V DeviceBus for ODVA DeviceNet				
Stranded TC Conductors (19x29) • XLPE Insulation (Thermoset) • PE Insulation (Thermoplastic) • Overall Beldfoil Shielding plus an overall tinned copper braid (65% coverage) • LSZH Outer Jacket				
Thermoset Jacket		TC-LS, TC-ER, AWM I/II A/B		
977896Z	2	0.80	19.8	
Thermoplastic Jacket		TC-LS, TC-ER		
777896T	2	0.80	19.8	

Conductor Color Coding: Data: Blue, White
Power: Red, Black

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff A/V and Electronic Cable



Delivering high-end audio and video quality in shipboard environments is critical to enhancing shipboard safety and communications as well as crew and consumer experience. Belden's ABS-rated audiovisual and electronic cables enable connectivity for the same wide range of application options available on dry land including audio, video, security, networking and control. Marine A/V cables use standard connectors, with no special installation techniques allowing for a fast and easy installation.

Products Include

- Electronic Audio, Control, and Instrumentation
- Audio and Speaker Cable
- Coaxial Broadcast AV
- DataTwist Nonbonded-Pair
- Security Composite

Key Attributes

- ABS certified
- LSZH jackets on all cables and options
- 10 year warranty

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff Electronic Audio, Control and Instrumentation Cable



Featured Options:


- Low Smoke Zero Halogen jacket – standard on all products
- RS-232 Cable (9451SB)
- Audio/Control Cables
- Multimedia control cable for AMX® and Crestron systems with both RS-485® and power in one cable (1502SB)

Certifications/Compliance

- ABS Certified
- Compliant with IEEE 45 and applicable sections of IEC 60092-376
- NEC/CEC CMG-LS
- FT4
- RoHS compliant

Construction:

1. LSZH Thermoplastic Jacket
2. 100% Foil Shield Coverage
3. Drain Wires



MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff Electronic Audio, Control and Instrumentation Cable



Part No.	AWG	Pairs	Insulation	Shield	OD (Nom)		Additional Features/Ratings
					Inch	mm	
Electronic Audio, Control, and Instrumentation Single- and Multi-pair Cables							
Standard (7x) TC Conductors • Thermoplastic LSZH Jacket							
9451SB*	22	1	PP	Beldfoil	0.16	4.1	300V RMS, NEC/CEC CMG-LS, FT4
8723SB*	22	2	PP	Individual Beldfoil	0.20	5.0	
8777SB	22	3	PP	Individual Beldfoil	0.27	6.9	UL AWM Style 2919, NEC/CEC CMG-LS, FT4
Electronic Audio, Control, and Instrumentation Multimedia Control Cable							
Standard (7x) TC Conductors • Thermoplastic LSZH Jacket							
1502SB	22	1 + 2C	FPR (data) F-R PVC (Power)	Beldfoil (data), Unshielded (power)	0.26	6.5	NEC/CEC CMG-LS, FT4

* Indicates common part numbers, LSZH, Thermoplastic

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff Audio and Speaker Cable



Featured Options:


- Low Smoke Zero Halogen thermoplastic jacket – standard on all products
- AES/EBU Audio Cable
- High-strand Speaker Cable

Certifications/Compliance

- ABS Certified
- Compliant with IEEE 45 and applicable sections of IEC 60092-376
- NEC/CEC CMG-LS
- FT4
- RoHS compliant
- High Flex/High Purity (Fine Stranding) on 1314SB-1317SB

Construction:

1. LSZH Thermoplastic Jacket
2. Datalene or Polypropylene Insulation
3. 100% Foil Shield Coverage (where applicable)
4. Drain Wires



MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff Audio and Speaker Cable



Part No.	AWG	Conductors	Insulation	Shield	OD (Nom)		Additional Features/Ratings
					Inch	mm	
AES/EBU Digital Audio Cable							
Standard TC Conductors • Thermoplastic LSZH Jacket							
1350SB*	24	1 PR	Datalene	Beldfoil	0.18	4.6	NEC/CEC CMG-LS, FT4
High Strand Speaker Cable for Unshielded Audio and Control; High-Flex and High-Purity							
Standard TC Conductors • Thermoplastic LSZH Jacket							
1314SB*	14	2	PP	Unshielded	0.30	7.6	NEC/CEC CMG-LS, FT4
1315SB	14	4	PP	Unshielded	0.34	8.6	
1316SB*	12	2	PP	Unshielded	0.34	8.6	
1317SB	12	4	PP	Unshielded	0.39	9.9	

* Indicates common part numbers, LSZH, Thermoplastic

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff Coaxial Broadcast AV Cable




Featured Options:

- Low Smoke Zero Halogen thermoplastic jacket – standard on all products
- CATV, Series
- RG-8 Type Low Loss 50 Ohm Wireless RF Transmission
- RG-6/U Type Digital Low Loss Serial
- RG-11/U Type Low Loss Serial
- Aluminum or Tinned Copper Braid Shielding

Certifications/Compliance

- ABS Certified
- Compliant with IEEE 45 and applicable sections of IEC 60092-376
- NEC/CEC CMG-LS
- FT4
- RoHS compliant



Construction:

1. **LSZH Thermoplastic Jacket**
2. **Foam Polyethylene or Foam High-Density Polyethylene Insulation**
3. **100% Duobond II® or Duofoil® Shield Coverage**
4. **60% or 95% Braid Shield Coverage**



MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff Coaxial Broadcast AV Cable



Part No.	AWG	Pairs	Insulation	Shield	OD (Nom)		Additional Features/Ratings
					Inch	mm	
Broadband Coaxial; CATV Series 6							
Thermoplastic LSZH Jacket							
9116SB*	18	Coax	Foam PE	Duobond®II + Aluminum Braid Shield	0.27	7.0	NEC/CEC CMG-LS, FT4
Low Loss 50 Ohm Wireless RF Transmission Cable; RG-8 Type							
Thermoplastic LSZH Jacket							
7810SB	10	Coax	Foam HDPE	Duobond®II + TC Braid	0.41	10.3	RF400, NEC/CEC CMG-LS, FT4
Precision Video Cable for Analog and Digital; Low Loss Serial Digital Coax; RG-6/U Type							
Thermoplastic LSZH Jacket							
1694SB*	18	Coax	Foam HDPE	Duofoil® + TC Braid	0.27	7.0	SDI/HDTV Digital Video, NEC/CEC CMG-LS, FT4
Precision Video Cable for Analog and Digital; Low Loss Serial Digital Coax; RG-11/U Type							
Thermoplastic LSZH Jacket							
7731SB	14	Coax	Foam HDPE	Duofoil® + TC Braid	0.40	10.2	SDI/HDTV Digital Video, NEC/CEC CMG-LS, FT4

* Indicates common part numbers, LSZH, Thermoplastic

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff DataTwist® Nonbonded Pair



Featured Options:


- Low Smoke Zero Halogen thermoplastic jacket – standard on all products
- Category 5e or Category 6
- Multimedia control cable for AMX® and Crestron systems with both RS-485® and power in one cable (1502SB)
- Shielded or Unshielded (depending on construction)
- RJ-45 Compatible

Certifications/Compliance

- ABS Certified
- TIA/EIA-568-B.2 or B.2.1
- Compliant with IEEE 45 and applicable sections of IEC 60092-376
- NEC/CEC CMG-LS
- FT4
- RoHS compliant

Construction:

1. LSZH Thermoplastic Jacket
2. 100% Foil Shield Coverage (for shielded)
3. Drain Wire (for shielded)
4. Rip Cord (for unshielded)



MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff DataTwist Nonbonded Pair



Part No.	AWG	Pairs	Insulation	Shield	OD (Nom)		Additional Features/Ratings
					Inch	mm	
Category 5e; TIA/EIA-568-B.2							
Solid BC Conductors • Thermoplastic LSZH Jacket							
1300SB*	24	4	P0	Beldfoil	0.26	6.6	NEC/CEC CMG-LS, FT4
1633ESB*	24	4	P0	Beldfoil + TC Braid	0.25	6.3	
1318SB	24	4	P0	Unshielded	0.29	7.4	
Category 6; TIA/EIA-568-B.2.1							
Standard TC Conductors • Thermoplastic LSZH Jacket							
1319SB*	23	4	P0	Unshielded	0.29	7.4	NEC/CEC CMG-LS, FT4

* Indicates common part numbers, LSZH, Thermoplastic

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff Security Composite Cable



Featured Options:


- Low Smoke Zero Halogen thermoplastic jacket – standard
- RG-6 Coax Plus Twisted Pair
- CCTV Plus Audio or Pan/Tilt/Zoom CCTV Control Applications

Certifications/Compliance

- ABS Certified
- NEC/CEC CMG-LS
- FT4
- RoHS compliant

Construction:

1. LSZH Thermoplastic Jacket



MarineTuff

Security Composite Cable



Part No.	AWG	Conductors	Insulation	Shield	OD (Nom)		Additional Features/Ratings
					Inch	mm	
CCTV plus Audio or Pan/Tilt/Zoom CCTV Control Applications							
RG6 Coax plus Twisted Pair - Siamese Construction							
1306SB*	18 (Coax) 18 (Pair)	1PR + Coax	FPE (Coax), PO (Pair)	BC Braid (Coax) Unshielded (Pair)	.28 x .51	7.0 x 13.1	NEC/CEC CMG-LS, FT4

* Indicates common part numbers, LSZH, Thermoplastic

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff Part Number Index



Part Number	Page No	Part Number	Page No	Part Number	Page No	Part Number	Page No
1037Z	38	2129Z	52	28081ZS	23	28140Z	27
1038Z	36	2130T	52	28082Z	21	28141Z	27
1039Z	38	2130Z	52	28082ZS	23	28142Z	27
1040Z	38	2131T	52	28083Z	21	28143Z	27
1041Z	38	2131Z	52	28084Z	21	28144Z	27
1042Z	38	3064Z	37	28085Z	21	28145Z	27
1043Z	38	3072T	64	28086Z	21	28146Z	27
1044Z	38	3072Z	64	28087Z	21	28147Z	27
1045Z	38	3076T	50	28088Z	21	28148Z	27
1046Z	38	3076Z	50	28089Z	21	28149Z	29
1047Z	38	3079T	55	28090Z	21	28150Z	29
1048Z	36	3079Z	55	28091Z	21	28151Z	29
1049Z	36	3080Z	41	28092Z	21	28152Z	30
1050Z	36	3081Z	41	28093Z	21	28153Z	30
1051Z	36	3088Z	36	28094Z	21	28154Z	30
1052Z	36	3089Z	37	28095Z	21	28155Z	31
1053Z	36	3090Z	38	28096Z	21	28156Z	31
1054Z	36	3091Z	39	28097Z	21	28157Z	31
1055Z	38	3092FT	61	28098Z	21	28158Z	32
1093Z	37	3092FZ	61	28099Z	21	28159Z	32
1094Z	37	3092T	61	28100Z	21	28160Z	32
1095Z	37	3092Z	61	28101Z	21	28161Z	33
1096Z	37	3103A	42	28102Z	21	28167Z	33
1097Z	39	3105T	58	28103Z	21	28168Z	33
1098Z	39	3105Z	58	28104Z	21	28169Z	33
1099Z	39	3107T	58	28105Z	21	28170Z	33
1100Z	39	3107Z	58	28106Z	21	28171Z	33
1118Z	38	3108T	58	28107Z	21	28172Z	33
1119Z	39	3108Z	58	28108Z	21	28173Z	34
1120Z	36	3109T	58	28110Z	24	28174Z	34
1121Z	37	3109Z	58	28111Z	24	28175Z	34
1300SB	76	3118Z	39	28112Z	24	28176Z	34
1306SB	78	3130Z	39	28113Z	24	28177Z	34
1314SB	72	7731SB	74	28114Z	24	28178Z	34
1315SB	72	7810SB	74	28115Z	24	28323Z	18
1316SB	72	7896T	67	28116Z	24	28324Z	18
1317SB	72	7896Z	67	28117Z	24	28326Z	15
1318SB	76	7940T	12	28118Z	24	28326ZS	17
1319SB	76	7940Z	12	28119Z	24	28327Z	15
1350SB	72	7953T	12	28120Z	24	28328Z	15
1502SB	70	7953Z	12	28121Z	24	28329Z	15
1633ESB	76	8723SB	70	28122Z	24	28330Z	18
1694SB	74	8777SB	70	28123Z	24	28331Z	18
2118T	50	9116SB	74	28124Z	24	28331ZS	20
2118Z	50	9451SB	70	28125Z	24	28334Z	15
2119T	50	27080Z	21	28126Z	24	28334ZS	17
2119Z	50	27109Z	24	28127Z	24	28335Z	15
2120T	50	27138Z	27	28128Z	24	28336Z	15
2120Z	50	27325Z	15	28129Z	24	28338Z	18
2121T	50	27325ZS	17	28130Z	24	28339Z	18
2121Z	50	27337Z	18	28131Z	24	28340Z	18
2122T	50	27337ZS	20	28132Z	24	28341Z	18
2122Z	50	27636Z	21	28133Z	24	28600Z	15
2127T	52	27641Z	24	28134Z	24	28601Z	15
2127Z	52	27643Z	27	28135Z	24	28602Z	15
2128T	52	27916Z	15	28136Z	24	28603Z	15
2128Z	52	27917Z	18	28137Z	24	28604Z	15
2129T	52	28081Z	21	28139Z	27	28605Z	15

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff Part Number Index



Part Number	Page No	Part Number	Page No	Part Number	Page No	Part Number	Page No
28606Z	15	773108T	58	W1043Z	39	W28094Z	23
28607Z	15	773109T	58	W1044Z	39	W28095Z	23
28608Z	15	777896T	67	W1045Z	39	W28096Z	23
28609Z	15	777940T	12	W1046Z	39	W28097Z	23
28610Z	15	777953T	12	W1047Z	39	W28098Z	23
28611Z	15	972118Z	51	W1048Z	36	W28099Z	23
28612Z	15	972119Z	51	W1049Z	36	W28100Z	23
28613Z	15	972120Z	51	W1050Z	36	W28101Z	23
28614Z	15	972121Z	51	W1051Z	36	W28102Z	23
28615Z	18	972122Z	51	W1052Z	36	W28103Z	23
28616Z	18	972127Z	52	W1053Z	36	W28104Z	23
28617Z	18	972128Z	52	W1054Z	36	W28105Z	23
28618Z	18	972129Z	52	W1055Z	39	W28106Z	23
28619Z	18	972130Z	52	W1093Z	37	W28107Z	23
28620Z	18	972131Z	52	W1094Z	37	W28108Z	23
28621Z	18	973072Z	64	W1095Z	37	W28110Z	26
28622Z	18	973076Z	50	W1096Z	37	W28111Z	26
28623Z	18	973079Z	55	W1097Z	40	W28112Z	26
28624Z	18	973092F	61	W1098Z	40	W28113Z	26
28625Z	18	973092Z	61	W1099Z	40	W28114Z	26
28626Z	18	973105Z	58	W1100Z	40	W28115Z	26
28627Z	18	973107Z	58	W1118Z	39	W28116Z	26
28628Z	18	973108Z	58	W1119Z	40	W28117Z	26
28629Z	21	973109Z	58	W1120Z	36	W28118Z	26
28630Z	24	977896Z	67	W1121Z	37	W28119Z	26
28632Z	15	977940Z	12	W3064Z	37	W28120Z	26
28634Z	24	977953Z	12	W3080Z	41	W28121Z	26
28912Z	21	B9A830	8	W3081Z	41	W28122Z	26
29500X	45	B9A831	8	W3088Z	36	W28123Z	26
29501X	45	B9A832	8	W3089Z	37	W28124Z	26
29502X	45	B9A833	8	W3090Z	39	W28125Z	26
29503X	45	B9A834	8	W3091Z	40	W28126Z	26
29504X	45	B9B830	8	W3103A	42	W28127Z	26
29505X	45	B9B831	8	W3118Z	40	W28128Z	26
29506X	45	B9B832	8	W3130Z	40	W28129Z	26
29507X	45	B9B833	8	W27080Z	23	W28130Z	26
29528X	47	B9B834	8	W27109Z	26	W28131Z	26
29529X	47	B9C830	8	W27138Z	28	W28132Z	26
29530X	47	B9C831	8	W27325Z	16	W28133Z	26
29531X	47	B9C832	8	W27337Z	19	W28134Z	26
29532X	47	B9C833	8	W27636Z	23	W28135Z	26
772118T	51	B9C834	8	W27641Z	26	W28136Z	26
772119T	51	B9E830	8	W27643Z	28	W28137Z	26
772120T	51	B9E831	8	W27916Z	16	W28139Z	28
772121T	51	B9E832	8	W27917Z	19	W28140Z	28
772122T	51	B9E833	8	W28081Z	23	W28141Z	28
772127T	52	B9E834	8	W28082Z	23	W28142Z	28
772128T	52	B9W830	8	W28083Z	23	W28143Z	28
772129T	52	B9W831	8	W28084Z	23	W28144Z	28
772130T	52	B9W832	8	W28085Z	23	W28145Z	28
772131T	52	B9W833	8	W28086Z	23	W28146Z	28
773072T	64	B9W834	8	W28087Z	23	W28147Z	28
773076T	50	W1037Z	39	W28088Z	23	W28148Z	28
773079T	55	W1038Z	36	W28089Z	23	W28152Z	30
773092F	61	W1039Z	39	W28090Z	23	W28153Z	30
773092T	61	W1040Z	39	W28091Z	23	W28154Z	30
773105T	58	W1041Z	39	W28092Z	23	W28155Z	31
773107T	58	W1042Z	39	W28093Z	23	W28156Z	31

MarineTuff™

Offshore and Marine Cable Solutions



MarineTuff Part Number Index



Part Number	Page No	Part Number	Page No	Part Number	Page No	Part Number	Page No
W28157Z	31	W28626Z	20	Z3091Z	39	Z28126Z	25
W28158Z	32	W28627Z	20	Z3103A	42	Z28127Z	25
W28159Z	32	W28628Z	20	Z3118Z	39	Z28128Z	25
W28160Z	32	W28629Z	23	Z3130Z	39	Z28129Z	25
W28161Z	33	W28630Z	26	Z27080Z	22	Z28130Z	25
W28167Z	33	W28632Z	17	Z27109Z	25	Z28131Z	25
W28168Z	33	W28634Z	26	Z27138Z	27	Z28132Z	25
W28169Z	33	W28912Z	23	Z27325Z	15	Z28133Z	25
W28170Z	33	W29500X	45	Z27337Z	18	Z28134Z	25
W28171Z	33	W29501X	45	Z27636Z	22	Z28135Z	25
W28172Z	33	W29502X	45	Z27641Z	25	Z28136Z	25
W28173Z	34	W29503X	45	Z27643Z	27	Z28137Z	25
W28174Z	34	W29504X	45	Z27916Z	15	Z28139Z	27
W28175Z	34	W29505X	45	Z27917Z	18	Z28140Z	27
W28176Z	34	W29506X	45	Z28081Z	22	Z28141Z	27
W28177Z	34	W29507X	45	Z28082Z	22	Z28142Z	27
W28178Z	34	W29528X	47	Z28083Z	22	Z28143Z	27
W28323Z	19	W29529X	47	Z28084Z	22	Z28144Z	27
W28324Z	20	W29530X	47	Z28085Z	22	Z28145Z	27
W28326Z	16	W29531X	47	Z28086Z	22	Z28146Z	27
W28327Z	16	W29532X	47	Z28087Z	22	Z28147Z	27
W28328Z	16	Z1037Z	38	Z28088Z	22	Z28148Z	27
W28329Z	16	Z1038Z	36	Z28089Z	22	Z28152Z	30
W28330Z	19	Z1039Z	38	Z28090Z	22	Z28153Z	30
W28331Z	19	Z1040Z	38	Z28091Z	22	Z28154Z	30
W28334Z	16	Z1041Z	38	Z28092Z	22	Z28155Z	31
W28335Z	16	Z1042Z	38	Z28093Z	22	Z28156Z	31
W28336Z	16	Z1043Z	38	Z28094Z	22	Z28157Z	31
W28338Z	19	Z1044Z	38	Z28095Z	22	Z28158Z	32
W28339Z	19	Z1045Z	38	Z28096Z	22	Z28159Z	32
W28340Z	19	Z1046Z	38	Z28097Z	22	Z28160Z	32
W28341Z	19	Z1047Z	38	Z28098Z	22	Z28161Z	33
W28600Z	16	Z1048Z	36	Z28099Z	22	Z28167Z	33
W28601Z	16	Z1049Z	36	Z28100Z	22	Z28168Z	33
W28602Z	16	Z1050Z	36	Z28101Z	22	Z28169Z	33
W28603Z	16	Z1051Z	36	Z28102Z	22	Z28170Z	33
W28604Z	16	Z1052Z	36	Z28103Z	22	Z28171Z	33
W28605Z	16	Z1053Z	36	Z28104Z	22	Z28172Z	33
W28606Z	16	Z1054Z	36	Z28105Z	22	Z28173Z	34
W28607Z	16	Z1055Z	38	Z28106Z	22	Z28174Z	34
W28608Z	17	Z1093Z	37	Z28107Z	22	Z28175Z	34
W28609Z	17	Z1094Z	37	Z28108Z	22	Z28176Z	34
W28610Z	17	Z1095Z	37	Z28110Z	25	Z28177Z	34
W28611Z	17	Z1096Z	37	Z28111Z	25	Z28178Z	34
W28612Z	17	Z1097Z	39	Z28112Z	25	Z28323Z	18
W28613Z	17	Z1098Z	39	Z28113Z	25	Z28324Z	19
W28614Z	17	Z1099Z	39	Z28114Z	25	Z28326Z	15
W28615Z	19	Z1100Z	39	Z28115Z	25	Z28327Z	15
W28616Z	19	Z1118Z	38	Z28116Z	25	Z28328Z	16
W28617Z	19	Z1119Z	39	Z28117Z	25	Z28329Z	16
W28618Z	19	Z1120Z	36	Z28118Z	25	Z28330Z	19
W28619Z	19	Z1121Z	37	Z28119Z	25	Z28331Z	18
W28620Z	19	Z3064Z	37	Z28120Z	25	Z28334Z	15
W28621Z	19	Z3080Z	41	Z28121Z	25	Z28335Z	15
W28622Z	19	Z3081Z	41	Z28122Z	25	Z28336Z	15
W28623Z	19	Z3088Z	36	Z28123Z	25	Z28338Z	18
W28624Z	19	Z3089Z	37	Z28124Z	25	Z28339Z	18
W28625Z	19	Z3090Z	38	Z28125Z	25	Z28340Z	18

MarineTuff™

Offshore and Marine Cable Solutions

MarineTuff Part Number Index



Part Number	Page No
Z28341Z	19
Z28600Z	15
Z28601Z	15
Z28602Z	16
Z28603Z	16
Z28604Z	16
Z28605Z	16
Z28606Z	16
Z28607Z	16
Z28608Z	16
Z28609Z	16
Z28610Z	16
Z28611Z	16
Z28612Z	16
Z28613Z	16
Z28614Z	16
Z28615Z	18
Z28616Z	18
Z28617Z	18
Z28618Z	19
Z28619Z	19
Z28620Z	19
Z28621Z	19
Z28622Z	19
Z28623Z	19
Z28624Z	19
Z28625Z	19
Z28626Z	19
Z28627Z	19
Z28628Z	19
Z28629Z	22
Z28630Z	25
Z28632Z	16
Z28634Z	25
Z28912Z	22
Z29500X	45
Z29501X	45
Z29502X	45
Z29503X	45
Z29504X	45
Z29505X	45
Z29506X	45
Z29507X	45
Z29528X	47
Z29529X	47
Z29530X	47
Z29531X	47
Z29532X	47
Z29503X	45
Z29504X	45
Z29505X	45
Z29506X	45
Z29507X	45
Z29528X	47
Z29529X	47
Z29530X	47
Z29531X	47
Z29532X	47

Part Number	Page No
Z3064Z	37
Z3080Z	41
Z3081Z	41
Z3088Z	36
Z3089Z	37
Z3090Z	38
Z3091Z	39
Z3103A	42
Z3118Z	39
Z3130Z	39



GLOBAL LOCATIONS

For worldwide Industrial Sales
and Technical Support, visit:
www.belden.com



UNITED STATES

Division Headquarters - Americas

2200 U.S. Highway 27 South
Richmond, IN 47374

Phone: 765-983-5200
Inside Sales: 800-235-2261
Fax: 765-983-5294
info@belden.com
www.belden.com

Belden Brand

2200 U.S. Highway 27 South
Richmond, IN 47374

Phone: 1-800-BELDEN-1
(1-800-235-3361)

Phone: 765-983-5200
Fax: 765-983-5294
info@belden.com

Industrial Networking GarrettCom & Hirschmann

47823 Westinghouse Drive
Fremont, CA 94539

Phone: (510) 438-9071
Fax: (510) 438-9072
Email: GClmktg@garrettcom.com

CANADA

National Business Center

2280 Alfred-Nobel
Suite 200
Saint-Laurent, QC
Canada H4S 2A4

Phone: 514-822-2345
Fax: 514-822-7979

LATIN AMERICA and the CARIBBEAN ISLANDS

Regional Offices
6100 Hollywood Boulevard
Suite 110
Hollywood, Florida 33024

Phone: 954-987-5044
Fax: 954-987-8022
salesla@belden.com

EUROPE/MIDDLE EAST/ AFRICA

Division Headquarters - EMEA

Edisonstraat 9
5928 PG Venlo, 5900 AA, Postbus 9
The Netherlands

Phone: +31-773-878-555
Fax: +31-773-878-448
venlo.salesinfo@belden.com
www.beldenemea.com

Regional Offices

Manchester International Office
Centre, Suite 13
Styal Road
Manchester M22 5WB
United Kingdom

Phone: +44-61-4983749
Fax: +344-161-4983762
manchester.salesinfo@belden.com

Location Neckartenzlingen -
Stuttgarter Straße 45-51
72654 Neckartenzlingen
Germany

Phone: +49-(0)-7127 / 14-0
Fax: +44-161-4983762
Fax: +49-(0)-7127 / 14-1313
inet-sales@belden.com

ASIA-PACIFIC

Division Headquarters - APAC

7/F Harbour View 2
16 Science Park East Avenue
Hong Kong Science Park
Shatin, Hong Kong

Phone: 852 2955-0128
Fax: 852-2907-6933
hongkong.sales@belden.com

Regional Offices

Unit 301 No. 19 Building,
1515 Gu Mei Road
Caohejing High-tech Park
Shanghai 200233
People's Republic of China

Phone: 021-54452388
Fax: 021-54452366/77
hongkong.sales@belden.com

101 27 International Business Park

05-01 iQuest @ IBM
Singapore 609924

Phone: 65-6879-9800
Fax: 65-6251-5010
singapore.sales@belden.com